


ADVANCED CABLE TIES PART NUMBER			A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	ANSI/UL 94 MH FLAMABILITY RATING	
AP(R, L)-AM6-9-C			.771 (19.600mm) +/- .020 (.520mm)	.197 (5.000mm) +/- .011 (.300mm)	.146 (3.700mm) +/- .011 (.300mm)	.204 (5.200mm) +/- .011 (.300mm)	.374 (9.500mm) +/- .014 (.360mm)	V-2	
						 ADVANCED CABLE TIES – ANCHOR MOUNT			
						COLOR DESIGNATIONS: 9 = NATURAL		MATERIAL: NYLON 6/6 POLYAMIDE	
						SHEET 1 OF 1	REV.: A	DRAWING NO.: AM6-A	
A	6/13/17	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	6/13/2017	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.93.0