


4" Head Configuration



6" & 8" Head Configuration

| ADVANCED CABLE TIES PART NUMBER | BUNDLE DIAMETER | | A IN (mm) +/- .030 (.889mm) | B IN (mm) +/- .010 (.250mm) | C IN (mm) +/- .030 (.889mm) | D IN (mm) +/- .010 (.250mm) | E IN (mm) +/- .014 (.360mm) | MIN LOOP TENSILE LBS (n) | ANSI/UL 94 MH FLAMABILITY RATING | |
|---------------------------------|------------------|----|-----------------------------------|-----------------------------------|-----------------------------------|--|-----------------------------------|--|----------------------------------|-------|
| | MAX IN (mm) | | | | | | | | | |
| AP(R, L)-04-BD-9 | .985 (25.019mm) | | 4.075 (103.50mm) | .050 (1.270mm) | 3.250 (82.55mm) | .101 (2.565mm) | .197 (5.003mm) | 18 (80) | V-2 | |
| AP(R, L)-06-BD-9 | 1.418 (36.017mm) | | 5.750 (146.05mm) | .062 (1.574mm) | 5.135 (130.429mm) | .110 (2.794mm) | .310 (7.874mm) | 30 (133) | V-2 | |
| AP(R, L)-08-BD-9 | 2.045 (51.943mm) | | 7.875 (200.025mm) | .066 (1.676mm) | 7.718 (196.056mm) | .110 (2.794mm) | .310 (7.874mm) | 40 (178) | V-2 | |
| | | | | | |  ACT ADVANCED CABLE TIES, INC. | | | | |
| | | | | | | BEADED CABLE TIES | | | | |
| | | | | | | COLOR DESIGNATIONS: 9 = NATURAL | | MATERIAL: NYLON 6/6 POLYAMIDE | | |
| C | 3/20/18 | PB | EG | EG | UPDATED TO VENDOR SPECS | | DRAWING NO.: BD-C | | | |
| B | 4/27/17 | JA | KT | KT | NEW LOGO ADDED. | | SHEET 1 OF 1 | REV.: C | | |
| A | 4/28/14 | JA | KT | KT | INITIAL RELEASE | | DRAWN BY | DATE | CHECK | SCALE |
| REV | DATE | BY | CHK | APPROVE | DESCRIPTION | | JA | 4/27/17 | KT | NONE |

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.69.2