


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETERS		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .020 (.508mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .030 (.762mm)	G IN (mm) +/- .020 (.508mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MATERIAL FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)									
AP(R,L)-08-120-BH-IT-30	.334 (8.5mm)	2.00 (50.9mm)	7.87 (200.0mm)	.065 (1.65mm)	.30 (7.6mm)	.43 (10.9mm)	.079 (2.0mm)	.952 (24.18mm)	.276 (7.0mm)	120 (534)	HB
AP(R,L)-11-120-BH-IT-30	.334 (8.5mm)	3.25 (82.8mm)	11.81 (300.0mm)	.065 (1.65mm)	.30 (7.6mm)	.43 (10.9mm)	.079 (2.0mm)	.952 (24.18mm)	.276 (7.0mm)	120 (534)	HB
AP(R,L)-14-120-BH-IT-30	.334 (8.5mm)	4.07 (103.5mm)	14.56 (370.0mm)	.065 (1.65mm)	.30 (7.6mm)	.43 (10.9mm)	.079 (2.0mm)	.952 (24.18mm)	.276 (7.0mm)	120 (534)	HB
 <b>ADVANCED CABLE TIES, INC.</b>											
<b>BUTTON HEAD CABLE TIES</b>											
<b>COLOR DESIGNATIONS:</b> IT-30 = IMPACT RESISTANT HEAT STABILIZED UV BLACK								<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>			
						SHEET 1 OF 1	REV.: A		DRAWING NO.: BH-120-A		
A	1/29/19	KT	DW	DW	INITIAL RELEASE	DRAWN BY	DATE		CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	KT	1/29/2019		DW	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.