



| ADVANCED CABLE TIES PART NUMBER | BUNDLE DIAMETER | | COATING | A - LENGTH IN (mm) | B - WIDTH IN (mm) | C - THICKNESS IN (mm) | D - HEAD SIZE IN (mm) | MAX OPERATING TEMPERATURE F (C) | MIN OPERATING TEMPERATURE F (C) | MIN LOOP TENSILE LBS (n) | REGULATORY APPROVALS | | | |
|--|-------------------|----------------------|-----------|-----------------------|---------------------------------------|--------------------------|---|--|---|-----------------------------|-------------------------|--|-------|--|
| | MIN IN (mm) | MAX IN (mm) | | | | | | | | | | | | |
| AL-08-100-SS-CT-C | .500 (12.70mm) | 1.960 (50.000mm) | POLYESTER | 7.870 (200.000mm) | .180 (4.600mm) | .013 (.330mm) | .255 (6.46mm) | 302 (150) | -76 (-60) | 150 (665) | UL TYPE-2 | | | |
| AL-14-100-SS-CT-C | .500 (12.70mm) | 3.930 (100.000mm) | POLYESTER | 14.170 (360.000mm) | .180 (4.600mm) | .013 (.330mm) | .255 (6.46mm) | 302 (150) | -76 (-60) | 150 (665) | UL TYPE-2 | | | |
| AL-20-100-SS-CT-C | .500 (12.70mm) | 5.900 (150.000mm) | POLYESTER | 20.470 (520.000mm) | .180 (4.600mm) | .013 (.330mm) | .255 (6.46mm) | 302 (150) | -76 (-60) | 150 (665) | UL TYPE-2 | | | |
| AL-27-100-SS-CT-C | .500 (12.70mm) | 7.870 (200.000mm) | POLYESTER | 26.770 (680.000mm) | .180 (4.600mm) | .013 (.330mm) | .255 (6.46mm) | 302 (150) | -76 (-60) | 150 (665) | UL TYPE-2 | | | |
| AL-08-250-SS-CT-C | .500 (12.70mm) | 1.960 (50.000mm) | POLYESTER | 7.870 (200.000mm) | .310 (7.900mm) | .013 (.330mm) | .404 (10.26mm) | 302 (150) | -76 (-60) | 300 (1,335) | UL TYPE-2 | | | |
| AL-14-250-SS-CT-C | .500 (12.70mm) | 3.930 (100.000mm) | POLYESTER | 14.170 (360.000mm) | .310 (7.900mm) | .013 (.330mm) | .404 (10.26mm) | 302 (150) | -76 (-60) | 300 (1,335) | UL TYPE-2 | | | |
| AL-20-250-SS-CT-C | .500 (12.70mm) | 5.900 (150.000mm) | POLYESTER | 20.470 (520.000mm) | .310 (7.900mm) | .013 (.330mm) | .404 (10.26mm) | 302 (150) | -76 (-60) | 300 (1,335) | UL TYPE-2 | | | |
| AL-27-250-SS-CT-C | .500 (12.70mm) | 7.870 (200.000mm) | POLYESTER | 26.770 (680.000mm) | .310 (7.900mm) | .013 (.330mm) | .404 (10.26mm) | 302 (150) | -76 (-60) | 300 (1,335) | UL TYPE-2 | | | |
|  | | | | | | | | | | | | | | |
| ADVANCED CABLE TIES – COATED STAINLESS STEEL CABLE TIES | | | | | | | | | | | | | | |
| E | 6/14/19 | DW | RB | RB | REMOVED AL-06-100-SS-CT-C | | MATERIAL DESIGNATION: SS = STAINLESS STEEL | | MATERIAL: 316 STAINLESS STEEL | | | | | |
| D | 4/29/17 | JA | KT | KT | NEW LOGO ADDED | | | | | | | | | |
| C | 5/23/16 | JA | KT | KT | REVISED AL-06-100-SS-CT-C DIMENSIONS. | | SHEET 1 OF 1 | | REV.: E | | DRAWING NO.: SS-CT-E | | | |
| B | 2/22/16 | JA | KT | KT | ADDED AL-06-100-SS-CT-C | | DRAWN BY | | DATE | | CHECK | | SCALE | |
| A | 5/1/14 | JA | KT | KT | INITIAL RELEASE | | JA | | 6/14/2019 | | RB | | NONE | |
| REV | DATE | BY | CHK | APPROVE | DESCRIPTION | | | | | | | | | |

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.