


ADVANCED CABLE TIES PART NUMBER				A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	TAB	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-CM4TNA250F-N-C				.96 (24.4mm)	.45 (11.4mm)	.22 (5.6mm)	.140 (3.56mm)	.054 (1.37mm)	.250 X .032	RED/NYLON	22-18	UL
AL-CM4TNB250F-N-C				.96 (24.4mm)	.45 (11.4mm)	.25 (6.4mm)	.140 (3.56mm)	.084 (2.13mm)	.250 X .032	BLUE/NYLON	16-14	UL
									 ACT ADVANCED CABLE TIES, INC.			
									DOUBLE CRIMP NYLON FULLY INSULATED MALE DISCONNECTS			
									COLOR: RED, BLUE		MATERIAL: NYLON	
B	10/21/21	DW	RB	RB	ISO DOC				SHEET 1 OF 1	REV.: B	DRAWING NO.: DC-FI-NY-M-DC-B	
A	6/13/14	JA	KT	KT	INITIAL RELEASE				DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION				JA	6/13/14	KT	NONE
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.												

SPC-4.10.109.2