


ADVANCED CABLE TIES PART NUMBER		A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY	
AL-B4A-N-C		1.035 (26.28mm)	.675 (17.14mm)	.059 (1.49mm)	.130 (3.30mm)	RED/NYLON	22-18	UL	
AL-B4B-N-C		1.080 (27.43mm)	.675 (17.14mm)	.091 (2.31mm)	.160 (4.06mm)	BLUE/NYLON	16-14	UL	
AL-B4C-N-C		1.300 (33.02mm)	.827 (21.00mm)	.138 (3.50mm)	.223 (5.66mm)	YELLOW/NYLON	12-10	UL	
									
						DOUBLE CRIMP NYLON INSULATED BUTT CONNECTORS			
						<b>COLOR:</b> RED, BLUE & YELLOW		<b>MATERIAL:</b> NYLON	
B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: NY-BC-B	
A	5/28/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	5/28/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.  
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.