


ADVANCED CABLE TIES PART NUMBER					A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D-Min. IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	PLUG DIAMETER	WIRE RANGE	REGULATORY	
AL-FSCA-156F-N-C					1.02 (25.9mm)	.42 (10.66mm)	.125 (3.18mm)	.062 (1.57mm)	.31 (7.9mm)	RED/NYLON	.156 (3.96)	22-18	UR	
AL-FSC-156F-N-C					1.02 (25.9mm)	.42 (10.66mm)	.145 (3.68mm)	.085 (2.16mm)	.31 (7.9mm)	BLUE/NYLON	.156 (3.96)	16-14	UR	
AL-FSC1-180F-N-C					1.02 (25.9mm)	.42 (10.66mm)	.145 (3.68mm)	.085 (2.16mm)	.31 (7.9mm)	BLUE/NYLON	.180 (4.57)	16-14	UR	
										DOUBLE CRIMP NYLON INSULATED FEMALE SNAP PLUGS				
														<b>COLOR:</b> RED & BLUE
B	10/21/21	DW	RB	RB	ISO DOC					SHEET 1 OF 1	<b>REV.: B</b>		DRAWING NO.: NY-FM-SP-B	
A	6/12/14	JA	KT	KT	INITIAL RELEASE					DRAWN BY	DATE	CHECK	SCALE	
<b>REV</b>	<b>DATE</b>	<b>BY</b>	<b>CHK</b>	<b>APPROVE</b>	<b>DESCRIPTION</b>					JA	6/12/14	KT	NONE	
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b> <b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>														