



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B-Min. IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-S4A-6-N-C	1.070 (27.18mm)	.062 (1.57mm)	.140 (3.56mm)	.546 (13.87mm)	.303 (7.70mm)	.146 (3.71mm)	.316 (8.02mm)	RED/NYLON	22-18	UL
AL-S4A-10-N-C	1.070 (27.18mm)	.062 (1.57mm)	.140 (3.56mm)	.546 (13.87mm)	.303 (7.70mm)	.198 (5.03mm)	.316 (8.02mm)	RED/NYLON	22-18	UL
AL-S4B-6-N-C	1.062 (26.97mm)	.081 (2.06mm)	.170 (4.32mm)	.546 (13.87mm)	.269 (6.83mm)	.146 (3.71mm)	.362 (9.19mm)	BLUE/NYLON	16-14	UL
AL-S4B-10-N-C	1.062 (26.97mm)	.081 (2.06mm)	.170 (4.32mm)	.546 (13.87mm)	.269 (6.83mm)	.198 (5.03mm)	.388 (9.85mm)	BLUE/NYLON	16-14	UL
AL-S4C-6-N-C	1.232 (31.29mm)	.128 (3.25mm)	.225 (5.72mm)	.669 (16.99mm)	.301 (7.65mm)	.146 (3.71mm)	.375 (9.53mm)	YELLOW/NYLON	12-10	UL
AL-S4C-10-N-C	1.232 (31.29mm)	.128 (3.25mm)	.225 (5.72mm)	.669 (16.99mm)	.301 (7.65mm)	.198 (5.03mm)	.375 (9.53mm)	YELLOW/NYLON	12-10	UL



DOUBLE CRIMP NYLON INSULATED SPADE TERMINALS

COLOR:
RED, BLUE & YELLOW

MATERIAL:
NYLON

B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: DC-NY-SP-TERM-B		
A	6/6/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	6/6/14	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.115.2