



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETERS				A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	MIN LOOP TENSILE LBS (n) 1 st Loop 2 nd Loop	ANSI/UL 94 MH FLAMABILITY RATING
	LOOP #1 MIN IN (mm)	LOOP #1 MAX IN (mm)	LOOP #2 MIN IN (mm)	LOOP #2 MAX IN (mm)							
AP(R, L)-08-50-DH-9	.140 (3.50mm)	2.15 (57.10mm)	.140 (3.50mm)	2.04 (52.00mm)	7.93 (201.61mm) +/- .098 (2.50mm)	6.496 (164.998mm) +/- .059 (1.50mm)	6.312 (160.324mm) +/- .059 (1.50mm)	.190 (4.82mm) +/- .012 (.30mm)	.052 (1.32mm) +/- .010 (.25mm)	50 (230) 40 (178)	V-2
AP(R, L)-08-50-DH-0	.140 (3.50mm)	2.15 (57.10mm)	.140 (3.50mm)	2.04 (52.00mm)	7.93 (201.61mm) +/- .098 (2.50mm)	6.496 (164.998mm) +/- .059 (1.50mm)	6.312 (160.324mm) +/- .059 (1.50mm)	.190 (4.82mm) +/- .012 (.30mm)	.052 (1.32mm) +/- .010 (.25mm)	50 (230) 40 (178)	V-2
AP(R, L)-11-50-DH-9	.140 (3.50mm)	3.36 (85.30mm)	.140 (3.50mm)	2.99 (76.00mm)	11.93 (303.21mm) +/- .098 (2.50mm)	10.496 (266.598mm) +/- .098 (2.50mm)	10.312 (261.924mm) +/- .098 (2.50mm)	.193 (4.90mm) +/- .012 (.30mm)	.052 (1.32mm) +/- .010 (.25mm)	50 (230) 40 (178)	V-2
AP(R, L)-11-50-DH-0	.140 (3.50mm)	3.36 (85.30mm)	.140 (3.50mm)	2.99 (76.00mm)	11.93 (303.21mm) +/- .098 (2.50mm)	10.496 (266.598mm) +/- .098 (2.50mm)	10.312 (261.924mm) +/- .098 (2.50mm)	.193 (4.90mm) +/- .012 (.30mm)	.052 (1.32mm) +/- .010 (.25mm)	50 (230) 40 (178)	V-2



DOUBLE HEAD SERIES CABLE TIES

COLOR DESIGNATIONS:

0 = UV BLACK 9 = NATURAL

MATERIAL:

NYLON 6/6 POLYAMIDE

B	11/12/18	KT	DW	DW	Update Vendor Specifications	SHEET 1 OF 1	REV.: B	DRAWING NO.: DH-50-B			
A	4/23/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE		
REV	DATE	B Y	CHK	APPROVE	DESCRIPTION	JA	4/23/2014	KT	NONE		

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.