


ADVANCED CABLE TIES PART NUMBER					A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	COLOR	COPPER COND. RANGE	REGULATORY	
AL-B4A-HS-C					.185 (4.70mm)	.280 (7.11mm)	1.55 (39.4mm)	.059 (1.50mm)	RED	22-18	UL	
AL-B4B-HS-C					.195 (4.95mm)	.308 (7.82mm)	1.55 (39.4mm)	.091 (2.31mm)	BLUE	16-14	UL	
AL-B4C-HS-C					.275 (6.99mm)	.383 (9.73mm)	1.80 (45.7mm)	.139 (3.53mm)	YELLOW	12-10	UL	
												
									HEAT SHRINK BUTT CONNECTORS			
									COLOR: RED, BLUE & YELLOW		MATERIAL: HEAT SHRINK	
B	10/21/21	DW	RB	RB	ISO DOC				SHEET 1 OF 1	REV.: B	DRAWING NO.: HS-BC-B	
A	6/26/14	JA	KT	KT	INITIAL RELEASE				DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION				JA	6/26/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.118.2