



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	COLOR	COPPER COND. RANGE	REGULATORY			
AL-CFR4NA250F-HS-Q	1.442 (36.627mm)	.230 (5.842mm)	.085 (2.159mm)	.380 (9.652mm)	RED	22-18	UL/CSA			
AL-CFR4NB250F-HS-Q	1.456 (36.982mm)	.230 (5.842mm)	.085 (2.159mm)	.385 (9.779mm)	BLUE	16-14	UL/CSA			
AL-CFR4NC250F-HS-Q	1.453 (36.906mm)	.315 (8.001mm)	.147 (3.734mm)	.370 (9.398mm)	YELLOW	12-10	UL/CSA			
										
					ADVANCED CABLE TIES – HEAT SHRINK FULLY INSULATED FEMALE DISCONNECTS					
					COLOR: RED, BLUE & YELLOW		MATERIAL: HEAT SHRINKABLE TUBING			
					SHEET 1 OF 1	REV.: A	DRAWING NO.: HS-FI-FM-DC-A			
A	6/27/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	6/27/14	KT	NONE
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.										