


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C-MIN. IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	TAB	COLOR	COPPER COND. RANGE	REGULATORY		
AL-CM4TNA250F-HS-Q	1.59 (40.4mm)	.17 (4.3mm)	.049 (1.25mm)	.45 (11.4mm)	.250 X .032	RED	22-18	UL		
AL-CM4TNB250F-HS-Q	1.59 (40.4mm)	.18 (4.5mm)	.082 (2.08mm)	.45 (11.4mm)	.250 X .032	BLUE	16-14	UL		
AL-CM4TNC250F-HS-Q	1.59 (40.4mm)	.23 (5.8mm)	.148 (3.76mm)	.46 (11.7mm)	.250 X .032	YELLOW	12-10	UL		
										
					HEAT SHRINK FULLY INSULATED MALE DISCONNECTS					
					COLOR: RED, BLUE & YELLOW		MATERIAL: HEAT SHRINK			
B	10/21/21	DW	RB	RB	ISO DOC		SHEET 1 OF 1	REV.: B	DRAWING NO.: HS-FI-M-DC-B	
A	6/27/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	6/27/14	KT	NONE
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.										