


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	COLOR	COPPER COND. RANGE	REGULATORY		
AL-CM4TNA250F-HS-Q	1.512 (38.405mm)	.225 (5.715mm)	.060 (1.524mm)	.445 (11.303mm)	RED	22-18	UL/CSA		
AL-CM4TNB250F-HS-Q	1.494 (37.948mm)	.230 (5.842mm)	.080 (2.032mm)	.445 (11.303mm)	BLUE	16-14	UL/CSA		
AL-CM4TNC250F-HS-Q	1.494 (37.948mm)	.300 (7.620mm)	.145 (3.683mm)	.455 (11.557mm)	YELLOW	12-10	UL/CSA		
									
					ADVANCED CABLE TIES – HEAT SHRINK FULLY INSULATED MALE DISCONNECTS				
					COLOR: RED, BLUE & YELLOW	MATERIAL: HEAT SHRINKABLE TUBING			
					SHEET 1 OF 1	REV.: A	DRAWING NO.: HS-FI-M-DC-A		
A	6/27/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	6/27/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.