



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D-MIN. IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	COLOR	COPPER COND. RANGE	REGULATORY
AL-R4A-10-HS-Q	1.46 (37.1mm)	.028 (.71mm)	.235 (5.97mm)	.064 (1.63mm)	.198 (5.03mm)	.320 (8.17mm)	RED	22-18	UL
AL-R4B-10-HS-Q	1.45 (36.8mm)	.031 (.79mm)	.235 (5.97mm)	.082 (2.08mm)	.198 (5.03mm)	.320 (8.17mm)	BLUE	16-14	UL
AL-R4B-14-HS-Q	1.63 (41.4mm)	.031 (.79mm)	.235 (5.97mm)	.082 (2.08mm)	.265 (6.73mm)	.475 (12.07mm)	BLUE	16-14	UL
AL-R4B-56-HS-Q	1.63 (41.4mm)	.031 (.79mm)	.235 (5.97mm)	.082 (2.08mm)	.328 (8.33mm)	.475 (12.07mm)	BLUE	16-14	UL
AL-R4B-38-HS-Q	1.68 (42.6mm)	.031 (.79mm)	.235 (5.97mm)	.082 (2.08mm)	.390 (9.91mm)	.544 (13.82mm)	BLUE	16-14	UL
AL-R4C-10-HS-Q	1.39 (35.1mm)	.031 (.79mm)	.310 (7.62mm)	.128 (3.25mm)	.198 (5.03mm)	.39 (9.9mm)	YELLOW	12-10	UL
AL-R4C-14-HS-Q	1.55 (39.4mm)	.031 (.79mm)	.310 (7.62mm)	.128 (3.25mm)	.265 (6.73mm)	.54 (13.7mm)	YELLOW	12-10	UL



HEAT SHRINK RING TERMINALS

COLOR:

RED, BLUE & YELLOW

MATERIAL:

HEAT SHRINK

B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: HS-RT-B	
A	6/26/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	6/26/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.  
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.