


NOTE: MAX TORQUE: 115 IN-LBS. (9.58 FT-LBS) WITH A .250" BOLT & WASHER

ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .010 (.254mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	H IN (mm) +/- .010 (.254mm)	MAX CABLE TIE WIDTH
AL/AR-SM120-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.127 (3.225mm)	.324 (8.229mm)	.338 (8.585mm)	.250 (6.350mm)	120 lb.
AL/AR-SM120-IT-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.127 (3.225mm)	.324 (8.229mm)	.338 (8.585mm)	.250 (6.350mm)	120 lb.
AL/AR-SM175-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.138 (3.505mm)	.363 (9.220mm)	.375 (9.525mm)	.250 (6.350mm)	175 lb.
AL/AR-SM175-IT-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.138 (3.505mm)	.363 (9.220mm)	.375 (9.525mm)	.250 (6.350mm)	175 lb.
AL/AR-SM250-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.150 (3.810mm)	.519 (13.183mm)	.533 (13.538mm)	.250 (6.350mm)	250 lb.
AL/AR-SM250-IT-30	1.441 (36.601mm)	.683 (17.348mm)	.308 (7.823mm)	.729 (18.516mm)	.150 (3.810mm)	.519 (13.183mm)	.533 (13.538mm)	.250 (6.350mm)	250 lb.
									
				ADVANCED CABLE TIES –HEAVY & EXTRA HEAVY DUTY SERIES SCREW MOUNTS					
				COLOR DESIGNATIONS: 30 = UV BLACK HEAT STABILIZED IT-30 = IMPACT RESISTANT, UV BLACK, HEAT STABILIZED			MATERIAL: NYLON 6/6 POLYAMIDE		
B	8/2/2017	JA	REMOVE NATURAL & AP DESIGNATIONS; ADDED NOTE REFERENCING TORQUE	SHEET 1 OF 1	REV.: B		DRAWING NO.: HD-SM-B		
A	6/12/17	JA	INITIAL RELEASE	DRAWN BY	DATE		CHECK	SCALE	
REV	DATE	BY	DESCRIPTION	JA	8/2/2017		KT	NONE	

SPC-4.10.92.1