


ADVANCED CABLE TIES PART NUMBER	WIRE RANGE		A	B	C	D	E	COLOR	MAX VOLTAGE	ANSI/UL 94 MII FLAMABILITY RATING	WORKING TEMPERATURE	REGULATORY APPROVALS
	MIN	MAX	IN (mm) + / - .007 (0.2 mm)	IN (mm) + / - .007 (0.2 mm)	IN (mm) + / - .007 (0.2 mm)	IN (mm) + / - .007 (0.2 mm)	IN (mm) + / - .007 (0.2 mm)					
AL-ACS-B1-M	3 #22 AWG	2 #16 AWG	.150 (3.810mm)	.256 (6.502mm)	.339 (8.610mm)	.228 (5.791mm)	.598 (15.189mm)	BLACK	300V	UL 94-V2	150°C	UL / CSA / RoHS
AL-ACS-B3-D	3 #20 AWG	2 #14 AWG /1 #16 AWG	.197 (5.003mm)	.382 (9.702mm)	.500 (12.700mm)	.307 (7.797mm)	.866 (21.996mm)	BLACK	300V	UL 94-V2	150°C	UL / CSA / RoHS
												
								<b>ADVANCED CABLE TIES – HIGH TEMPERATURE SCREW-ON WIRE CONNECTORS</b>				
								<b>SPRING INSERT:</b>  <b>STEEL</b>		<b>MATERIAL:</b>  <b>TOUGH THERMOPLASTIC</b>		
								SHEET 1 OF 1	REV.: A	DRAWING NO.: STDWC-A		
A	12/22/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA	12/22/14	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.