


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	F IN (mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MAX IN (mm)									
AP(R, L)-04-18-FL-9	.984 (25.000mm)		4.390 (111.500mm) +/- 1.000 (.039mm)	2.874 (73.000mm) +/- .039 (1.000mm)	.098 (2.500mm) +/- .010 (.250mm)	.976 (24.800mm) +/- .020 (.520mm)	.307 (7.800mm) +/- .014 (.307mm)	.047 (1.200mm) +/- .010 (.250mm)	18 (80)	V-2
AP(R, L)-05-18-FL-9	.984 (25.000mm)		5.122 (130.100mm) +/- 1.000 (.039mm)	2.874 (73.000mm) +/- .039 (1.000mm)	.094 (2.400mm) +/- .010 (.250mm)	.807 (20.5mm) +/- .020 (.520mm)	1.090 (27.700mm) +/- .020 (.520mm)	.043 (1.100mm) +/- .010 (.250mm)	18 (80)	V-2
										
						ADVANCED CABLE TIES – 18 LB. (80n) FLAG SERIES CABLE TIES				
						<b>COLOR DESIGNATIONS:</b> 9 = NATURAL		<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>		
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.		SHEET 1 OF 1	REV.: B		DRAWING NO.: 4/5-FL-B
A	4/29/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	4/27/17	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.70.1