





ImpACTie

Impact Resistant
High Temperature
UV Weatherable


Prevent downtime replacing ties from cracking and breaking due to repeated high impacts, vibration, extreme temperatures, or weathering.



Contact us for more information or samples:
Advanced Cable Ties, Inc.

800.861.7228 - www.advancedcableties.com - sales@actfs.com

ACT
ADVANCED CABLE TIES INC.



ImpACTie

Prevent

Cracking & Breaking

Caused by repeated High Impacts, Vibration, High Temperatures, & Weather

- Increased Flexibility and Toughness
- Resists High Impact Fatigue
- Endures Vibrations
- Resist Cold Temperature Fracturing Down to -40°F
- Provides High Operating Temperatures of 230°F
- Allows Cable Tie Installation at -4°F
- Weather Resistant UV Black for Outdoor Use and Sun Protection

Per Bag	ACT Part Number	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Diameter Inch/mm	Per Case
100	AL-05-40-IT-30-C	5.84/148.33	.14/3.55	.04/1.24	40 lb.	1.43/36.42	10,000
1000	AL-05-40-IT-30-M						
100	AL-07-50-IT-30-C	7.56/192.07	.18/4.57	.05/1.32	50 lb.	1.87/47.62	10,000
1000	AL-07-50-IT-30-M						
100	AL-11-50-IT-30-C	11.25/285.75	.18/4.57	.05/1.32	50 lb.	3.06/77.77	5,000
500	AL-11-50-IT-30-D						
100	AL-14-50-IT-30-C	14.25/361.95	.18/4.57	.05/1.32	50 lb.	4.00/101.60	5,000
500	AL-14-50-IT-30-D						
100	AL-08-120-IT-30-C	8.70/220.98	.30/7.62	.07/1.93	120 lb.	2.06/52.30	3,000
100	AL-14-120-IT-30-C	15.09/383.36	.30/7.62	.07/1.93	120 lb.	4.06/103.18	2,000
100	AL-07-50-MH-IT-30-C	8.00/203.20	.17/4.49	.05/1.32	50 lb.	1.75/44.45	5,000
100	AL-14-120-MH-IT-30-C	15.75/400.05	.29/7.56	.07/1.93	120 lb.	4.06/103.17	2,000

Tolerance: .xxx = +.005, .xx = +.015

Sold in case quantities



Advanced Cable Ties, Inc.

245 Suffolk Lane, Gardner, MA 01440

800.861.7228 . www.advancedcableties.com . sales@actfs.com



AP-LIT-IMPACT RESISTANT

