


ADVANCED CABLE TIES PART NUMBER			A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	TAB SIZE	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-CFR4NA250F-C			.89 (22.6mm)	.38 (9.7mm)	.23 (5.9mm)	.16 (4.1mm)	.080 (2.0mm)	.250" X .032"	RED/NYLON	22-18	UL
AL-CFR4NB250F-C			.89 (22.6mm)	.38 (9.7mm)	.23 (5.9mm)	.16 (4.1mm)	.080 (2.0mm)	.250" X .032"	BLUE/NYLON	16-14	UL
											
								NYLON FULLY INSULATED FEMALE DISCONNECTS			
								COLOR: RED, BLUE		MATERIAL: NYLON	
B	10/21/21	DW	RB	RB	ISO DOC			SHEET 1 OF 1	REV.: B	DRAWING NO.: DC-NY-FI-FM-DC-B	
A	6/13/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA	6/13/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.123.2