


ADVANCED CABLE TIES PART NUMBER		A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	TAB SIZE	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-CM4TNA250F-C		.97 (24.6mm)	.45 (11.4mm)	.23 (5.8mm)	.145 (3.68mm)	.054 (1.37mm)	.250" X .032"	RED/NYLON	22-18	UL
AL-CM4TNB250F-C		.97 (24.6mm)	.45 (11.4mm)	.23 (5.8mm)	.170 (4.32mm)	.083 (2.11mm)	.250" X .032"	BLUE/NYLON	16-14	UL
							 ACT ADVANCED CABLE TIES, INC.			
							NYLON FULLY INSULATED MALE DISCONNECTS			
							COLOR: RED & BLUE		MATERIAL: NYLON 6/6	
B	10/21/21	DW	RB	RB	ISO DOC		SHEET 1 OF 1	REV.: B		DRAWING NO.: NY-M-DIS-B
A	5/28/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	5/28/14	KT	NONE
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.										