



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-CM4TNA250F-C	.961 (24.409mm)	.146 (3.708mm)	.058 (1.473mm)	.220 (5.588mm)	.449 (11.405mm)	RED/NYLON	22-18	UL/CSA
AL-CM4TNB250F-C	.961 (24.409mm)	.175 (4.445mm)	.087 (2.210mm)	.220 (5.588mm)	.449 (11.405mm)	BLUE/NYLON	16-14	UL/CSA



ADVANCED CABLE TIES – NYLON FULLY INSULATED MALE DISCONNECTS

COLOR: RED & BLUE

MATERIAL:

NYLON 6/6

SHEET 1 OF 1

REV.: A

DRAWING NO.: NY-M-DIS-A

REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DRAWN BY	DATE	CHECK	SCALE
A	5/28/14	JA	KT	KT	INITIAL RELEASE	JA	5/28/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.