


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	MAX. PANEL THICKNESS	HOLE SIZE	LOOP TENSILE LBS (n)	MECHANICAL STRENGTH LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)											
AP(R, L)-07-50-PM-9	.138 (3.5mm)	1.97 (50.0mm)	7.93 (201.59mm) +/- .098 (2.50mm)	.187 (4.74mm) +/- .012 (.300mm)	.309 (7.84mm) +/- .014 (.360mm)	.054 (1.37mm) +/- .012 (.300mm)	.161 (4.10mm) +/- .012 (.30mm)	.153 (3.90mm)	.193 (4.90mm)	49 (220)	40 (178)	V-2	AH-2
AP(R, L)-07-50-PM-0	.138 (3.5mm)	1.97 (50.0mm)	7.93 (201.59mm) +/- .098 (2.50mm)	.187 (4.74mm) +/- .012 (.300mm)	.309 (7.84mm) +/- .014 (.360mm)	.054 (1.37mm) +/- .012 (.300mm)	.161 (4.10mm) +/- .012 (.30mm)	.153 (3.90mm)	.193 (4.90mm)	49 (220)	40 (178)	V-2	AH-2
													
								PUSH MOUNT SERIES CABLE TIES					
D	12/19/19	DW	RB	RB	MECHANICAL STRENGTH AND PANEL THICKNESS ADDITION			<b>COLOR DESIGNATIONS:</b> 0 = UV BLACK 9 = NATURAL		<b>MATERIAL:</b> NYLON 6/6 POLYAMIDE			
C	11/9/18	KT	DW	DW	UPDATED VENDOR SPECS								
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.			SHEET 1 OF 1	REV.: D		DRAWING NO.: PM-D		
A	12/22/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY	DATE		CHECK	SCALE	
REV	DATE	BY	CHK	APPROV E	DESCRIPTION			JA	4/27/2017		KT	NONE	
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b> <b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>													