


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	HOLE SIZE	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MII FLAMABILITY RATING	PLENUM RATING		
	MIN IN (mm)	MAX IN (mm)											
AP(R, L)-07-50-PM-9	.138 (3.5mm)	1.97 (50.0mm)	7.93 (201.59mm) +/- .098 (2.50mm)	.187 (4.74mm) +/- .012 (.300mm)	.309 (7.84mm) +/- .014 (.360mm)	.054 (1.37mm) +/- .012 (.300mm)	.161 (4.10mm) +/- .012 (.30mm)	.193 (4.90mm)	49 (220)	V-2	AH-2		
AP(R, L)-07-50-PM-0	.138 (3.5mm)	1.97 (50.0mm)	7.93 (201.59mm) +/- .098 (2.50mm)	.187 (4.74mm) +/- .012 (.300mm)	.309 (7.84mm) +/- .014 (.360mm)	.054 (1.37mm) +/- .012 (.300mm)	.161 (4.10mm) +/- .012 (.30mm)	.193 (4.90mm)	49 (220)	V-2	AH-2		
													
						PUSH MOUNT SERIES CABLE TIES							
						COLOR DESIGNATIONS: 0 = UV BLACK 9 = NATURAL			MATERIAL: NYLON 6/6 POLYAMIDE				
C	11/9/18	KT	DW	DW	UPDATED VENDOR SPECS								
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.			SHEET 1 OF 1		REV.: C			
A	12/22/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY		DATE			
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA		4/27/2017			
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.										CHECK		SCALE	
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.													