


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A - LENGTH IN (mm) +/- 2%	B - WIDTH IN (mm) +/- .20 (5.08mm)	C - HEAD SIZE IN (mm) +/- .20 (5.08mm)	D - THICKNESS IN (mm) +/- .02 (.508mm)	MAX OPERATING TEMPERATURE F (C)	MIN OPERATING TEMPERATURE F (C)	MIN LOOP TENSILE LBS (n)	REGULATORY APPROVALS
	MAX IN (mm)									
AL-08-100-SS-SP-C	1.970 (50.000mm)		7.870 (200.000mm)	.180 (4.600mm)	.255 (6.480mm)	.010 (.260mm)	1000 (538)	-112 (-80)	150 (665)	N/A
AL-14-100-SS-SP-C	3.940 (100.000mm)		14.170 (360.000mm)	.180 (4.600mm)	.255 (6.480mm)	.010 (.260mm)	1000 (538)	-112 (-80)	150 (665)	N/A
AL-20-100-SS-SP-C	5.900 (150.000mm)		20.470 (520.000mm)	.180 (4.600mm)	.255 (6.480mm)	.010 (.260mm)	1000 (538)	-112 (-80)	150 (665)	N/A
AL-08-250-SS-SP-C	1.970 (50.000mm)		7.870 (200.000mm)	.310 (7.900mm)	.380 (9.640mm)	.010 (.260mm)	1000 (538)	-112 (-80)	300 (1,335)	N/A
AL-14-250-SS-SP-C	3.940 (100.000mm)		14.170 (360.000mm)	.310 (7.900mm)	.380 (9.640mm)	.010 (.260mm)	1000 (538)	-112 (-80)	300 (1,335)	N/A
AL-20-250-SS-SP-C	5.900 (150.000mm)		20.470 (520.000mm)	.310 (7.900mm)	.380 (9.640mm)	.010 (.260mm)	1000 (538)	-112 (-80)	300 (1,335)	N/A
										
						A	5/23/16	JA	KT	KT
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	5/23/2016	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.88.0