


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A	B	C	D	E	F	G	H	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)		
AP(R, L)-05-30-TB-3	.875 (22.225mm)	1.437 (36.423mm)	5.840 (148.336mm)	.049 (1.244mm)	.140 (3.556mm)	.240 (6.096mm)	.175 (4.445mm)	.250 (6.350mm)	.092 (2.336mm)	.026 (.660mm)	40 (180)	V-2
												
ADVANCED CABLE TIES – TOTE BOX SERIES CABLE TIES												
COLOR DESIGNATIONS: 3 = ORANGE									MATERIAL: NYLON 6/6 POLYAMIDE			
B	5/2/17	JA	KT	KT	NEW LOGO ADDED		SHEET 1 OF 1	REV.: B		DRAWING NO.: TB-B		
A	4/8/15	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE		
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	5/2/17	KT	NONE		

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.