


ADVANCED CABLE TIES PART NUMBER		A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-FR4A250-C		.31 (7.9mm)	.42 (10.7mm)	.13 (3.3mm)	.865 (21.97mm)	.156 (3.96mm)	.31 (7.9mm)	RED/VINYL	22-18	UL
AL-FR4B250-C		.31 (7.9mm)	.42 (10.7mm)	.14 (3.6mm)	.865 (21.97mm)	.156 (3.96mm)	.31 (7.9mm)	BLUE/VINYL	16-14	UL
AL-FR4C250-C		.31 (7.9mm)	.56 (14.2mm)	.24 (6.1mm)	1.011 (25.68mm)	.156 (3.96mm)	.31 (7.9mm)	YELLOW/VINYL	12-10	UL
						 ACT ADVANCED CABLE TIES, INC.				
						VINYL INSULATED FEMALE DISCONNECTS				
						COLOR:		MATERIAL:		
						RED, BLUE & YELLOW		VYNYL 6/6		
B	10/21/21	DW	RB	RB	ISO DOC	SHEET 1 OF 1	REV.: B	DRAWING NO.: VI-FM-DIS-B		
A	5/28/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	5/28/14	KT	NONE	
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.										