


ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C-Min. IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	H IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-MT4A250-C	.450 (11.43mm)	.145 (3.68mm)	.062 (1.57mm)	.92 (23.4mm)	.075 (1.91mm)	.14 (3.6mm)	.30 (7.6mm)	.250 (6.35mm)	RED/VINYL	22-18	UL
AL-MT4B250-C	.450 (11.43mm)	.175 (4.44mm)	.081 (2.06mm)	.92 (23.4mm)	.075 (1.91mm)	.14 (3.6mm)	.30 (7.6mm)	.250 (6.35mm)	BLUE/VINYL	16-14	UL
AL-MT4C250-C	.550 (13.97mm)	.245 (6.22mm)	.128 (3.25mm)	1.10 (27.94mm)	.075 (1.91mm)	.14 (3.6mm)	.30 (7.6mm)	.250 (6.35mm)	YELLOW/VINYL	12-10	UL
					 ACT ADVANCED CABLE TIES, INC.						
					VINYL INSULATED MALE DISCONNECTS						
					COLOR:			MATERIAL:			
					RED, BLUE & YELLOW			VINYL			
B	10/21/21	DW	RB	RB	ISO DOC		SHEET 1 OF 1	REV.: B		DRAWING NO.: VI-M-DIS-B	
A	5/28/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	5/28/14	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.130.2