



ADVANCED CABLE TIES PART NUMBER	A IN (mm) +/- .005 (.127mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .005 (.127mm)	E IN (mm) +/- .005 (.127mm)	F IN (mm) +/- .005 (.127mm)	G IN (mm) +/- .005 (.127mm)	H IN (mm) +/- .005 (.127mm)	COLOR/MATERIAL	COPPER COND. RANGE	REGULATORY
AL-MT4A250-C	.458 (11.633mm)	.149 (3.784mm)	.056 (1.422mm)	.905 (22.987mm)	.072 (1.829mm)	.133 (3.378mm)	.305 (7.747mm)	.253 (6.426mm)	RED/VINYL	22-18	UL/CSA
AL-MT4B250-C	.548 (13.919mm)	.273 (6.934mm)	.131 (3.327mm)	1.050 (26.670mm)	.072 (1.829mm)	.120 (3.048mm)	.305 (7.747mm)	.253 (6.426mm)	BLUE/VINYL	16-14	UL/CSA
AL-MT4C250-C	.451 (11.455mm)	.185 (4.699mm)	.086 (2.184mm)	.899 (22.835mm)	.072 (1.829mm)	.132 (3.353mm)	.305 (7.747mm)	.253 (6.426mm)	YELLOW/VINYL	12-10	UL/CSA



ADVANCED CABLE TIES – VINYL INSULATED MALE DISCONNECTS

COLOR: RED, BLUE & YELLOW

MATERIAL:

VINYL

SHEET 1 OF 1

REV.: A

DRAWING NO.: VI-M-DIS-A

REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DRAWN BY	DATE	CHECK	SCALE
A	5/28/14	JA	KT	KT	INITIAL RELEASE	JA	5/28/14	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.