


HEAT STABILIZED TIES



HEAT STABILIZED TIES

Heat-Stabilized Nylon for High-Temperature Environments
with Temperatures up to 257°F

- Working temperatures from -40°F to 257°F
- High tensile strength with low insertion force
- Indoor and Outdoor use

Part Number	Color	Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Bundle Diameter Inch/mm	Tensile Strength lb./n.	Operating Temp. °F Min./Max.	MIL-SPEC	UL	CSA	Per Bag	Per Case
AL-04-18-30-M	UV Black	Heat Stabilized Nylon 66	4.12/104.77	0.09/2.41	0.04/1.06	0.87/22.22	18/80	-40 to 257	MS3367-4-11	Type 21	Type 21	1,000	10,000
AL-06-18-30-M	UV Black	Heat Stabilized Nylon 66	6.18/157.14	0.09/2.41	0.04/1.06	1.5/38.10	18/80	-40 to 257		Type 21	Type 21	1,000	10,000
AL-08-18-30-M	UV Black	Heat Stabilized Nylon 66	8.18/207.94	0.09/2.41	0.04/1.06	2.18/55.55	18/80	-40 to 257		Type 21	Type 21	1,000	10,000
AL-05-40-30-M	UV Black	Heat Stabilized Nylon 66	5.84/148.33	0.14/3.55	0.04/1.24	1.43/36.42	40/178	-40 to 257	MS3367-5-11	Type 21	Type 21	1,000	10,000
AL-08-40-30-M	UV Black	Heat Stabilized Nylon 66	8.87/225.42	0.14/3.55	0.04/1.24	2.37/60.32	40/178	-40 to 257		Type 21	Type 21	1,000	10,000
AL-11-40-30-D	UV Black	Heat Stabilized Nylon 66	10.96/278.58	0.14/3.55	0.05/1.37	3.37/85.72	40/178	-40 to 257		Type 21	Type 21	500	5,000
AL-14-40-30-D	UV Black	Heat Stabilized Nylon 66	14.25/361.95	0.14/3.55	0.05/1.37	4.00/101.60	40/178	-40 to 257		Type 21	Type 21	500	5,000
AL-07-50-30-M	UV Black	Heat Stabilized Nylon 66	7.56/192.07	0.18/4.57	0.05/1.32	1.87/47.62	50/222	-40 to 257	MS3367-1-11	Type 21	Type 21	1,000	10,000
AL-11-50-30-D	UV Black	Heat Stabilized Nylon 66	11.25/285.75	0.18/4.57	0.05/1.32	3.06/77.77	50/222	-40 to 257	MS3367-7-11	Type 21	Type 21	500	5,000
AL-14-50-30-D	UV Black	Heat Stabilized Nylon 66	14.35/364.49	0.18/4.57	0.05/1.32	4.00/101.60	50/222	-40 to 257	MS3367-2-11	Type 21	Type 21	500	5,000
AL-08-120-30-C	UV Black	Heat Stabilized Nylon 66	8.70/220.98	0.30/7.62	0.07/1.93	2.06/52.32	120/534	-40 to 257		Type 21S	Type 21S	100	3,000
AL-14-120-30-C	UV Black	Heat Stabilized Nylon 66	14.82/376.63	0.30/7.62	0.07/1.93	4.06/103.12	120/534	-40 to 257	MS3367-3-11	Type 21S	Type 21S	100	2,000

Related product lines



316 Stainless Steel
Cable Ties



Cold Weather



Nylon 12

ACT
ADVANCED CABLE TIES, INC.
245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com



intertek