


# HEAT STABILIZED TIES



## HEAT STABILIZED TIES

Heat-Stabilized Nylon for High-Temperature Environments  
with Temperatures up to 257°F

- Working temperatures from -40°F to 257°F
- High tensile strength with low insertion force
- Indoor and Outdoor use

| Part Number    | Color    | Material                 | Length<br>Inch/mm | Width<br>Inch/mm | Thickness<br>Inch/mm | Bundle<br>Diameter<br>Inch/mm | Tensile<br>Strength<br>lb-f/n. | Operating<br>Temp. °F<br>Min./Max. | MIL-SPEC    | UL       | CSA      | Per<br>Bag | Per<br>Case |
|----------------|----------|--------------------------|-------------------|------------------|----------------------|-------------------------------|--------------------------------|------------------------------------|-------------|----------|----------|------------|-------------|
| AL-04-18-30-M  | UV Black | Heat Stabilized Nylon 66 | 4.12/104.77       | 0.09/2.41        | 0.04/1.06            | 0.87/22.22                    | 18/80                          | -40 to 257                         | MS3367-4-11 | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-06-18-30-M  | UV Black | Heat Stabilized Nylon 66 | 6.18/157.14       | 0.09/2.41        | 0.04/1.06            | 1.5/38.10                     | 18/80                          | -40 to 257                         |             | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-08-18-30-M  | UV Black | Heat Stabilized Nylon 66 | 8.18/207.94       | 0.09/2.41        | 0.04/1.06            | 2.18/55.55                    | 18/80                          | -40 to 257                         |             | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-05-40-30-M  | UV Black | Heat Stabilized Nylon 66 | 5.84/148.33       | 0.14/3.55        | 0.04/1.24            | 1.43/36.42                    | 40/178                         | -40 to 257                         | MS3367-5-11 | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-08-40-30-M  | UV Black | Heat Stabilized Nylon 66 | 8.87/225.42       | 0.14/3.55        | 0.04/1.24            | 2.37/60.32                    | 40/178                         | -40 to 257                         |             | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-11-40-30-D  | UV Black | Heat Stabilized Nylon 66 | 10.96/278.58      | 0.14/3.55        | 0.05/1.37            | 3.37/85.72                    | 40/178                         | -40 to 257                         |             | Type 21  | Type 21  | 500        | 5,000       |
| AL-14-40-30-D  | UV Black | Heat Stabilized Nylon 66 | 14.25/361.95      | 0.14/3.55        | 0.05/1.37            | 4.00/101.60                   | 40/178                         | -40 to 257                         |             | Type 21  | Type 21  | 500        | 5,000       |
| AL-07-50-30-M  | UV Black | Heat Stabilized Nylon 66 | 7.56/192.07       | 0.18/4.57        | 0.05/1.32            | 1.87/47.62                    | 50/222                         | -40 to 257                         | MS3367-1-11 | Type 21  | Type 21  | 1,000      | 10,000      |
| AL-11-50-30-D  | UV Black | Heat Stabilized Nylon 66 | 11.25/285.75      | 0.18/4.57        | 0.05/1.32            | 3.06/77.77                    | 50/222                         | -40 to 257                         | MS3367-7-11 | Type 21  | Type 21  | 500        | 5,000       |
| AL-14-50-30-D  | UV Black | Heat Stabilized Nylon 66 | 14.35/364.49      | 0.18/4.57        | 0.05/1.32            | 4.00/101.60                   | 50/222                         | -40 to 257                         | MS3367-2-11 | Type 21  | Type 21  | 500        | 5,000       |
| AL-08-120-30-C | UV Black | Heat Stabilized Nylon 66 | 8.70/220.98       | 0.30/7.62        | 0.07/1.93            | 2.06/52.32                    | 120/534                        | -40 to 257                         |             | Type 21S | Type 21S | 100        | 3,000       |
| AL-14-120-30-C | UV Black | Heat Stabilized Nylon 66 | 14.82/376.63      | 0.30/7.62        | 0.07/1.93            | 4.06/103.12                   | 120/534                        | -40 to 257                         | MS3367-3-11 | Type 21S | Type 21S | 100        | 2,000       |

### Related product lines



316 Stainless Steel  
Cable Ties



Cold Weather



Nylon 12



ADVANCED CABLE TIES, INC.  
245 Suffolk Lane, Gardner, MA 01440  
Phone: 800.861.7228 - Fax: 978.630.3999  
sales@actfs.com



intertek