

MOUNTING HOLE CABLE TIES



MOUNTING HOLE CABLE TIES

Secures and positions wire bundles, cables, hoses, etc.
to panels or other surfaces

- Allows for quicker mechanical mounting and reduced cost
- Secure and position wire bundles to panels with one fastener
- Mechanical Strength: 50 lb-f Tensile = 30 lb-f / 120 lb-f Tensile = 60 lb-f
- 30 lb-f & 50 lb-f = UL Type 21 / 120 lb-f = UL Type 21S



ACT Part Number	Color & Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Tie Tensile	Screw Size	Max Bundle Diameter Inch/mm	Hole Diameter Inch/mm	Per Bag	Per Case
AL-05-30-MH-9-C*	Natural Nylon	6.12/155.5	.14/3.60	.043/1.109	40 lb-f 178 n.	#8	1.40/35.5	.155/3.93	100	10,000
AL-05-30-MH-0-C*	UV Black Nylon								100	
AL-08-50-MH-9-M	Natural Nylon	8.0/203.2	.177/4.495	.052/1.320	50 lb-f 222 n.	#10	1.87/47.6	.208/5.28	1,000	5,000
AL-08-50-MH-9-C	Nylon								100	
AL-08-50-MH-0-M	UV Black Nylon								1,000	
AL-08-50-MH-0-C	Nylon								100	
AL-12-50-MH-9-C	Natural Nylon	11.5/292.1	.177/4.495	.053/1.346	50 lb-f 222 n.	#10	3.06/77.7	.206/5.23	100	5,000
AL-12-50-MH-0-C	UV Black Nylon								100	
AL-15-50-MH-9-C	Natural Nylon	14.5/368.3	.177/4.495	.053/1.346	50 lb-f 222 n.	#10	4.00/101.6	.206/5.23	100	5,000
AL-15-50-MH-0-C	UV Black Nylon								100	
AL-15-120-MH-9-C	Natural Nylon	15.7/400.0	.298/7.569	.075/1.905	120 lb-f 534 n.	1/4"	4.06/103.1	.256/6.50	100	2,000
AL-15-120-MH-0-C	UV Black Nylon								100	


Tolerance: .xxx = $\pm .005$, .xx = $\pm .015$ - "5" made in China

Sold in case quantities

Related product lines



Cable Wrap



Split Loom



Screw Mounts

ACT
ADVANCED CABLE TIES, INC.
245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com

