

NYLON 12 CABLE TIES



NYLON 12 CABLE TIES

Specially Formulated for use in Solar and other Extreme Environmental Applications

- Molecularly designed for solar applications to withstand the harsh rays of the sun and corrosive outdoor elements
- Low water absorption and density maintains stability
- Ideal for galvanized steel surface contact
- Chemical resistant and insensitive to stress cracking
- Smooth edges eliminates abrasion damage



ACT Part Number	Color	Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Bundle Diameter Inch/mm	Tensile Strength	Per Bag	Per Case
AL-05-40-NY12-0-C	UV Black	Nylon 12	5.84/148.33	.140/3.556	.049/1.244	1.437/36.4	40 lb./178 n.	100	1000
AL-07-50-NY12-0-C	UV Black	Nylon 12	7.56/192.07	.180/4.572	.052/1.320	1.875/47.6	50 lb./222 n.	100	1000
AL-11-50-NY12-0-C	UV Black	Nylon 12	11.25/285.75	.180/4.572	.052/1.320	3.062/77.7	50 lb./222 n.	100	1000
AL-14-50-NY12-0-C	UV Black	Nylon 12	14.37/365.12	.180/4.572	.052/1.320	4.00/101.6	50 lb./222 n.	100	1000
AL-08-120-NY12-0-C	UV Black	Nylon 12	8.70/220.98	.300/7.620	.076/1.930	2.06/52.3	100 lb./444 n.	100	1000
AL-14-120-NY12-0-C	UV Black	Nylon 12	15.09/383.36	.300/7.620	.076/1.930	4.06/103.1	100 lb./444 n.	100	1000

Tolerance: .xxx = ±.005, .xx = ±.015, Fraction = ±1/32" Sold in case quantities.

Related product lines



Coated 316
Stainless Steel



UV Black
Nylon 6/6



Heat Stabilized
UV Black
Nylon 6/6



245 Suffolk Lane • Gardner, MA 01440
Phone: 800.861.7228 • Fax: 978.630.3999
sales@actfs.com

