

# NYLON 12 CABLE TIES



## NYLON 12 CABLE TIES

Specially Formulated for use in Solar and other Extreme Environmental Applications

- Molecularly designed for solar applications to withstand the harsh rays of the sun and corrosive outdoor elements
- Low water absorption and density maintains stability
- Ideal for galvanized steel surface contact
- Chemical resistant and insensitive to stress cracking
- Smooth edges eliminates abrasion damage



ACT Part Number	Color	Material	Length Inch/mm	Width Inch/mm	Thickness Inch/mm	Bundle Diameter Inch/mm	Tensile Strength	Per Bag	Per Case
AL-05-40-NY12-0-C	UV Black	Nylon 12	5.84/148.33	.14/3.55	.05/1.24	1.43/36.4	40 lb./178 n.	100	1000
AL-07-50-NY12-0-C	UV Black	Nylon 12	7.56/192.07	.18/4.57	.05/1.32	1.87/47.6	50 lb./222 n.	100	1000
AL-11-50-NY12-0-C	UV Black	Nylon 12	11.25/285.75	.18/4.57	.05/1.32	3.06/77.7	50 lb./222 n.	100	1000
AL-14-50-NY12-0-C	UV Black	Nylon 12	14.35/364.49	.18/4.57	.05/1.32	4.00/101.6	50 lb./222 n.	100	1000
AL-08-120-NY12-0-C	UV Black	Nylon 12	8.70/220.98	.30/7.62	.07/1.93	2.06/52.3	100 lb./444 n.	100	1000
AL-14-120-NY12-0-C	UV Black	Nylon 12	14.82/376.63	.30/7.62	.07/1.93	4.06/103.1	100 lb./444 n.	100	1000

Sold in case quantities.

### Related product lines



Coated 316  
Stainless Steel



UV Black  
Nylon 6/6



Heat Stabilized  
UV Black  
Nylon 6/6

**ACT**  
ADVANCED CABLE TIES, INC.  
245 Suffolk Lane, Gardner, MA 01440  
Phone: 800.861.7228 - Fax: 978.630.3999  
sales@actfs.com



intertek