

STAINLESS STEEL CABLE TIES



Applications - Communications, Power Utilities, Automotive, Transportation, Aerospace, Shipping, Construction, Industrial, Petroleum, Marine, Agriculture, Nuclear, Fire Protection, Signals, and Signs

316 Stainless Steel - Provides high resistance to heat, salts, and acids
- Perfect for indoor, outdoor, and underground applications

Polyester Coating - Enhances the corrosive properties and acts as a barrier to avoid corrosion between dissimilar metals

Operating Temps - Uncoated 1000F / 500C - Coated 302F / 150C

Tension Tool

ACT Part Number	Cable Tie Sizes & Type	Cut Off Type
AL-900	100 to 300 lb. 316 Stainless Steel	Manual Handle

Quickly Tensions And Cuts Off Excess Strap without leaving extremely sharp metal protrusion that will cause snags, cuts, and abrasions to cables, hoses, products, and users.

Saves Time

Automatically cuts off excess strap when the selected tension setting is achieved. Produces consistent tension from tie to tie and saves installation time with one easy pull of the trigger.





316 Coated Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-06-100-SS-CT-C	Stainless Steel	5.90/150.0	.180/4.6	.009"/.25mm	150 lb.	1.53/39.0	UL	1,000
100	AL-08-100-SS-CT-C	Stainless Steel	7.87/200.0	.180/4.6	.009"/.25mm	150 lb.	1.96/50.0	UL	1,000
100	AL-14-100-SS-CT-C	Stainless Steel	14.17/360.0	.180/4.6	.009"/.25mm	150 lb.	3.93/100.0	UL	1,000
100	AL-20-100-SS-CT-C	Stainless Steel	20.47/520.0	.180/4.6	.009"/.25mm	150 lb.	5.90/150.0	UL	1,000
100	AL-27-100-SS-CT-C	Stainless Steel	26.77/680.0	.180/4.6	.009"/.25mm	150 lb.	7.87/200.0	UL	1,000
100	AL-08-250-SS-CT-C	Stainless Steel	7.87/200.0	.310/7.9	.009"/.25mm	300 lb.	1.96/50.0	UL	1,000
100	AL-14-250-SS-CT-C	Stainless Steel	14.17/360.0	.310/7.9	.009"/.25mm	300 lb.	3.93/100.0	UL	1,000
100	AL-20-250-SS-CT-C	Stainless Steel	20.47/520.0	.310/7.9	.009"/.25mm	300 lb.	5.90/150.0	UL	1,000
100	AL-27-250-SS-CT-C	Stainless Steel	26.77/680.0	.310/7.9	.009"/.25mm	300 lb.	7.87/200.0	UL	1,000

Thickness Including Coating .016"/.40mm Tolerance: $\pm .003"/0.076\text{mm}$, Made in USA, Sold in bag quantities, 150 lb = 665 n / 300 lb = 1335 n

316 Uncoated Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-06-100-SS-C	Stainless Steel	5.90/150.0	.180/4.6	.009"/.25mm	150 lb.	1.53/39.0	UL	1,000
100	AL-08-100-SS-C	Stainless Steel	7.87/200.0	.180/4.6	.009"/.25mm	150 lb.	1.96/50.0	UL	1,000
100	AL-14-100-SS-C	Stainless Steel	14.17/360.0	.180/4.6	.009"/.25mm	150 lb.	3.93/100.0	UL	1,000
100	AL-20-100-SS-C	Stainless Steel	20.47/520.0	.180/4.6	.009"/.25mm	150 lb.	5.90/150.0	UL	1,000
100	AL-27-100-SS-C	Stainless Steel	26.77/680.0	.180/4.6	.009"/.25mm	150 lb.	7.87/200.0	UL	1,000
100	AL-08-250-SS-C	Stainless Steel	7.87/200.0	.310/7.9	.009"/.25mm	300 lb.	1.96/50.0	UL	1,000
100	AL-14-250-SS-C	Stainless Steel	14.17/360.0	.310/7.9	.009"/.25mm	300 lb.	3.93/100.0	UL	1,000
100	AL-20-250-SS-C	Stainless Steel	20.47/520.0	.310/7.9	.009"/.25mm	300 lb.	5.90/150.0	UL	1,000
100	AL-27-250-SS-C	Stainless Steel	26.77/680.0	.310/7.9	.009"/.25mm	300 lb.	7.87/200.0	UL	1,000

Tolerance: $\pm .003"/.076\text{mm}$, Made in USA, Sold in bag quantities, 150 lb = 665 n / 300 lb = 1335 n

316 Coated Ladder Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-08-100-SS-LD-CT-C	Stainless Steel	7.87/200.0	.270/7.0	.011"/.30mm	250 lb.	2.36/60.0	UL	1,000
100	AL-14-100-SS-LD-CT-C	Stainless Steel	14.17/360.0	.270/7.0	.011"/.30mm	250 lb.	4.13/105.0	UL	1,000
100	AL-24-100-SS-LD-CT-C	Stainless Steel	24.01/610.0	.270/7.0	.011"/.30mm	250 lb.	5.90/150.0	UL	1,000
100	AL-30-100-SS-LD-CT-C	Stainless Steel	29.52/750.0	.270/7.0	.011"/.30mm	250 lb.	7.87/200.0	UL	1,000
100	AL-08-250-SS-LD-CT-C	Stainless Steel	7.87/200.0	.470/12.0	.013"/.35mm	450 lb.	2.36/60.0	UL	1,000
100	AL-14-250-SS-LD-CT-C	Stainless Steel	14.17/360.0	.470/12.0	.013"/.35mm	450 lb.	4.13/105.0	UL	1,000
100	AL-24-250-SS-LD-CT-C	Stainless Steel	24.01/610.0	.470/12.0	.013"/.35mm	450 lb.	5.90/150.0	UL	1,000
100	AL-30-250-SS-LD-CT-C	Stainless Steel	29.52/750.0	.470/12.0	.013"/.35mm	450 lb.	7.87/200.0	UL	1,000

Thickness Including Coating .018"/.45mm Tolerance: $\pm .003$ "/0.076mm, Made in SG, Sold in bag quantities, 100 lb = 444 n / 250 lb = 1112 n

316 Uncoated Ladder Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-08-100-SS-LD-C	Stainless Steel	7.87/200.0	.270/7.0	.011"/.30mm	250 lb.	2.36/60.0	UL	1,000
100	AL-14-100-SS-LD-C	Stainless Steel	14.17/360.0	.270/7.0	.011"/.30mm	250 lb.	4.13/105.0	UL	1,000
100	AL-24-100-SS-LD-C	Stainless Steel	24.01/610.0	.270/7.0	.011"/.30mm	250 lb.	5.90/150.0	UL	1,000
100	AL-30-100-SS-LD-C	Stainless Steel	29.52/750.0	.270/7.0	.011"/.30mm	250 lb.	7.87/200.0	UL	1,000
100	AL-08-250-SS-LD-C	Stainless Steel	7.87/200.0	.470/12.0	.013"/.35mm	450 lb.	2.36/60.0	UL	1,000
100	AL-14-250-SS-LD-C	Stainless Steel	14.17/360.0	.470/12.0	.013"/.35mm	450 lb.	4.13/105.0	UL	1,000
100	AL-24-250-SS-LD-C	Stainless Steel	24.01/610.0	.470/12.0	.013"/.35mm	450 lb.	5.90/150.0	UL	1,000
100	AL-30-250-SS-LD-C	Stainless Steel	29.52/750.0	.470/12.0	.013"/.35mm	450 lb.	7.87/200.0	UL	1,000

Thickness Including Coating .018"/.45mm Tolerance: $\pm .003$ "/0.076mm, Made in SG, Sold in bag quantities, 100 lb = 444 n / 250 lb = 1112 n

316 Coated Spring Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-08-100-SS-SP-CT-C	Stainless Steel	7.87/200.0	.180/4.6	.009"/.25mm	150 lb.	1.97/50.0		1,000
100	AL-14-100-SS-SP-CT-C	Stainless Steel	14.17/360.0	.180/4.6	.009"/.25mm	150 lb.	3.94/100.0		1,000
100	AL-20-100-SS-SP-CT-C	Stainless Steel	20.47/520.0	.180/4.6	.009"/.25mm	150 lb.	5.90/150.0		1,000
100	AL-08-250-SS-SP-CT-C	Stainless Steel	7.87/200.0	.310/7.9	.009"/.25mm	300 lb.	1.97/50.0		1,000
100	AL-14-250-SS-SP-CT-C	Stainless Steel	14.17/360.0	.310/7.9	.009"/.25mm	300 lb.	3.94/100.0		1,000
100	AL-20-250-SS-SP-CT-C	Stainless Steel	20.47/520.0	.310/7.9	.009"/.25mm	300 lb.	5.90/150.0		1,000

Thickness Including Coating .016"/.40mm Tolerance: $\pm .003$ "/0.076mm, Made in SG, Sold in bag quantities, 100 lb = 444 n / 250 lb = 1112 n

316 Uncoated Spring Stainless Steel Cable Ties

Per Bag	ACT Part Number	Material	Length Inch/mm	Width Inch/mm	Metal Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Case
100	AL-08-100-SS-SP-C	Stainless Steel	7.87/200.0	.180/4.6	.009"/.25mm	150 lb.	1.97/50.0		1,000
100	AL-14-100-SS-SP-C	Stainless Steel	14.17/360.0	.180/4.6	.009"/.25mm	150 lb.	3.94/100.0		1,000
100	AL-20-100-SS-SP-C	Stainless Steel	20.47/520.0	.180/4.6	.009"/.25mm	150 lb.	5.90/150.0		1,000
100	AL-08-250-SS-SP-C	Stainless Steel	7.87/200.0	.310/7.9	.009"/.25mm	300 lb.	1.97/50.0		1,000
100	AL-14-250-SS-SP-C	Stainless Steel	14.17/360.0	.310/7.9	.009"/.25mm	300 lb.	3.94/100.0		1,000
100	AL-20-250-SS-SP-C	Stainless Steel	20.47/520.0	.310/7.9	.009"/.25mm	300 lb.	5.90/150.0		1,000

Tolerance: $\pm .003$ "/0.076mm, Made in SG, Sold in bag quantities, 100 lb = 444 n / 250 lb = 1112 n

Additional Product Lines



Advanced Cable Ties, Inc.
 245 Suffolk Lane, Gardner, MA 01440
 800-861-7228 - sales@actfs.com - www.advancedcableties.com

