

STAINLESS STEEL CABLE TIES



STAINLESS STEEL CABLE TIES

Provide Unique Engineering Solutions for Demanding Applications
with High Temperatures and Corrosive Environments

- Available in Uncoated or Polyester-Coated 316 Stainless Steel
- 316 Stainless Steel - High resistance to heat, salts, & acids; perfect for indoor, outdoor, & underground applications
- Polyester Coating - Enhances the corrosive properties and acts as a barrier to avoid corrosion between dissimilar metals
- Applications - Communications, power utilities, solar, automotive, transportation, aerospace, shipping, construction, industrial, petroleum, marine, agriculture, nuclear, fire protection, signals, and signs

Uncoated Stainless Steel Cable Ties

ACT Part Number	Length Inch/mm	Width Inch/mm	Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Bag	Per Case
AL-06-100-SS-C	5.90/150.0	.180/4.6	.010"/.26mm	150 lb-f	1.53/39.0	UL	100	1,000
AL-08-100-SS-C	7.87/200.0	.180/4.6	.010"/.26mm	150 lb-f	1.96/50.0	UL	100	1,000
AL-14-100-SS-C	14.17/360.0	.180/4.6	.010"/.26mm	150 lb-f	3.93/100.0	UL	100	1,000
AL-20-100-SS-C	20.47/520.0	.180/4.6	.010"/.26mm	150 lb-f	5.90/150.0	UL	100	1,000
AL-27-100-SS-C	26.77/680.0	.180/4.6	.010"/.26mm	150 lb-f	7.87/200.0	UL	100	1,000
AL-08-250-SS-C	7.87/200.0	.310/7.9	.010"/.26mm	300 lb-f	1.96/50.0	UL	100	1,000
AL-14-250-SS-C	14.17/360.0	.310/7.9	.010"/.26mm	300 lb-f	3.93/100.0	UL	100	1,000
AL-20-250-SS-C	20.47/520.0	.310/7.9	.010"/.26mm	300 lb-f	5.90/150.0	UL	100	1,000
AL-27-250-SS-C	26.77/680.0	.310/7.9	.010"/.26mm	300 lb-f	7.87/200.0	UL	100	1,000

Coated Stainless Steel Cable Ties

ACT Part Number	Length Inch/mm	Width Inch/mm	Thickness	Tie Tensile	Diameter Inch/mm	UL-CSA Mil-Spec	Per Bag	Per Case
AL-08-100-SS-CT-C	7.87/200.0	.180/4.6	.013"/.33mm	150 lb-f	1.96/50.0	UL	100	1,000
AL-14-100-SS-CT-C	14.17/360.0	.180/4.6	.013"/.33mm	150 lb-f	3.93/100.0	UL	100	1,000
AL-20-100-SS-CT-C	20.47/520.0	.180/4.6	.013"/.33mm	150 lb-f	5.90/150.0	UL	100	1,000
AL-27-100-SS-CT-C	26.77/680.0	.180/4.6	.013"/.33mm	150 lb-f	7.87/200.0	UL	100	1,000
AL-08-250-SS-CT-C	7.87/200.0	.310/7.9	.013"/.33mm	300 lb-f	1.96/50.0	UL	100	1,000
AL-14-250-SS-CT-C	14.17/360.0	.310/7.9	.013"/.33mm	300 lb-f	3.93/100.0	UL	100	1,000
AL-20-250-SS-CT-C	20.47/520.0	.310/7.9	.013"/.33mm	300 lb-f	5.90/150.0	UL	100	1,000
AL-27-250-SS-CT-C	26.77/680.0	.310/7.9	.013"/.33mm	300 lb-f	7.87/200.0	UL	100	1,000

Tolerance: $\pm .003"/0.076\text{mm}$, 150 lb-f = 665 n / 300 lb-f = 1335 n Operating Temp. SS -76° to 572°F / SS-CT -76° to 302°F Sold in bag quantities



Related product lines



Tension Tool



Nylon 12



Cold Weather

ACT
ADVANCED CABLE TIES, INC.
245 Suffolk Lane, Gardner, MA 01440
Phone: 800.861.7228 - Fax: 978.630.3999
sales@actfs.com

