


ADVANCED CABLE TIE'S PART NUMBER	BUNDLE DIAMETER		A IN (mm)	B IN (mm)	C IN (mm)	D IN (mm)	E IN (mm)	HOLE SIZE IN (mm)	MIN LOOP TENSILE LBS (n)	MECHANICAL STRENGTH LBS (n)	MAX. PANEL THICKNESS IN (mm)	ANSI/UL 94 MH FLAMABILITY RATING	
	MIN IN (mm)	MAX IN (mm)											
AP (R, L)-06-40-PMW-9		1.430 (36.322mm)	6.220 (157.988mm) +/- .05 (1.270mm)	.460 (11.684mm) +/- .02 (.508mm)	.140 (3.556mm) +/- .005 (.127mm)	.165 (4.191mm) +/- .015 (.381mm)	.047 (1.194mm) +/- .005 (.127mm)	.181 (4.597mm) +/- .015 (.381mm)	40 (178)	30 (133)	.093 (2.40)	V-2	
AP (R, L)-06-40-PMW-0		1.430 (36.322mm)	6.220 (157.988mm) +/- .05 (1.270mm)	.460 (11.684mm) +/- .02 (.508mm)	.140 (3.556mm) +/- .005 (.127mm)	.165 (4.191mm) +/- .015 (.381mm)	.047 (1.194mm) +/- .005 (.127mm)	.181 (4.597mm) +/- .015 (.381mm)	40 (178)	30 (133)	.093 (2.40)	V-2	
													
PUSH MOUNT WING SERIES CABLE TIES													
E	7/20/23	DT	RB	RB	REMOVED OBSOLETE PRODUCTS								
D	12/19/19	DW	RB	RB	MECHANICAL STRENGTH AND PANEL THICKNESS ADDITION				<b>COLOR DESIGNATIONS:</b>		<b>MATERIAL:</b>		
C	11/9/18	KT	DW	DW	UPDATE VENDOR SPECS & 7" WING DESIGN				0 = UV BLACK 9 = NATURAL 30 = HEAT STABILIZED		<b>NYLON 6/6 POLYAMIDE</b>		
B	5/1/17	JA	KT	KT	NEW LOGO ADDED				SHEET 1 OF 1	<b>REV.: E</b>		DRAWING NO.: PMW-E	
A	12/22/14	JA	KT	KT	INITIAL RELEASE				DRAWN BY	DATE		CHECK	SCALE
<b>REV</b>	<b>DATE</b>	<b>BY</b>	<b>CHK</b>	<b>APPROVE</b>	<b>DESCRIPTION</b>				JA	5/1/2017		KT	NONE
<b>CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.</b> <b>THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.</b>													

SPC-4.10.53.7