



ADVANCED CABLE TIES PART NUMBER			A IN (mm) +/- .014 (.35mm)	B IN (mm) +/- .010 (.25mm)	C IN (mm) +/- .010 (.25mm)	D IN (mm) +/- .010 (.25mm)	E IN (mm) +/- .010 (.25mm)	NOMINAL HOLE DIAMETER IN (mm)	PANEL THICKNESS	ANSI/UL 94 MH FLAMABILITY RATING
AP(R,L)-BM-0			.62 (15.8mm)	.28 (7.2mm)	.25 (6.2mm)	.299 (7.6mm)	.196 (5.0mm)	.25 (6.3)	.03 (0.8mm) to .12 (3.0mm)	V-2
						ADVANCED CABLE TIES - BUTTON MOUNT				
						COLOR DESIGNATION: 0 = Black		MATERIAL: NYLON 6/6 POLYAMIDE		
B	12-22-22	DW	RB	RB	MODIFIED DESIGN	SHEET 1 OF 1	REV.: A	DRAWING NO.: BM-B		
A	10/15/21	DW	RB	RB	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	DW	10/15/21	RB	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.