


ADVANCED CABLE TIES PART NUMBER					A IN (mm) +/- .020 (.52mm)	B IN (mm) +/- .012 (.30mm)	C IN (mm) +/- .012 (.30mm)	D IN (mm) +/- .020 (.52mm)	E IN (mm) +/- .012 (.30mm)	F IN (mm) +/- .012 (.30mm)	ANSI/UL 94 MH FLAMABILITY RATING		
AP(R, L)-LPM1-9-C					.75 (19.10mm)	.168 (4.26mm) #8 FLAT HEAD	.205 (5.20mm)	.500 (12.70mm)	.125 (3.17mm)	.062 (1.57mm)	V-2		
								 ACT ADVANCED CABLE TIES, INC.					
								ADVANCED CABLE TIES – LOW PROFILE SCREW MOUNT					
								COLOR DESIGNATIONS: 9 = NATURAL		MATERIAL: NYLON 6/6 POLYAMIDE			
					SHEET 1 OF 1		REV.: A		DRAWING NO.: LPM1				
A	12/21/22	DW	RB	RB	INITIAL RELEASE			DRAWN BY		DATE		CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			DW		12/21/2022		RB	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
 THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.