



ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A	B	C	D	E	F	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .250 (6.350mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .010 (.254mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)			
AP(R, L)-07-50-9	.06 (1.57mm)	1.87 (47.6mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-07-50-0	.06 (1.57mm)	1.87 (47.6mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-11-50-9	.06 (1.57mm)	3.06 (77.7mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-11-50-0	.06 (1.57mm)	3.06 (77.7mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-14-50-9	.06 (1.57mm)	4.00 (101.6mm)	14.350 (364.49mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-14-50-0	.06 (1.57mm)	4.00 (101.6mm)	14.350 (364.49mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2
AP(R, L)-17-50-9	.118 (2.99mm)	4.75 (120.65mm)	16.937 (430.199mm)	.055 (1.397mm)	.185 (4.69mm)	.330 (8.382mm)	.232 (5.892mm)	.300 (7.62mm)	50 (222)	V-2	
AP(R, L)-17-50-0	.118 (2.99mm)	4.75 (120.65mm)	16.937 (430.199mm)	.055 (1.397mm)	.185 (4.69mm)	.330 (8.382mm)	.232 (5.892mm)	.300 (7.62mm)	50 (222)	V-2	
AP(R, L)-21-50-9	.118 (2.99mm)	6.12 (155.57mm)	21.00 (533.4mm)	.055 (1.397mm)	.185 (4.69mm)	.330 (8.382mm)	.232 (5.892mm)	.300 (7.62mm)	50 (222)	V-2	
AP(R, L)-21-50-0	.118 (2.99mm)	6.12 (155.57mm)	21.00 (533.4mm)	.055 (1.397mm)	.185 (4.69mm)	.330 (8.382mm)	.232 (5.892mm)	.300 (7.62mm)	50 (222)	V-2	
G	3/10/23	DW	RB	RB	UPDATED TO MANUFACTURED SPECS		 <b>50 LB. (222n) STANDARD SERIES CABLE TIES</b>				
F	6/12/20	DW	RB	RB	UPDATE TENSILE RATING 17" AND 21"						
E	3/2/18	PB	EG	EG	UPDATE DIMENSION C +/- FROM .005 TO .010						
D	2/1/18	PB	EG	EG	UPDATED DIMENSION A +/- FROM .125 TO .250 AND OVERALL DIMENSION A FOR 14-50-X						
C	12/19/17	PB	VA	VA	UPDATED UL SPECS AND ADDED VENDOR SPECS		<b>COLOR DESIGNATIONS:</b> 0 = UV BLACK    9 = NATURAL		<b>MATERIAL:</b> <b>NYLON 6/6 POLYAMIDE</b>		
B	4/29/17	JA	KT	KT	NEW LOGO ADDED		SHEET 1 OF 1	<b>REV.: G</b>		DRAWING NO.: 50-G	
A	12/22/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE	
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	4/29/2017	KT	NONE	

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.