



Angled Tail Optional

ADVANCED CABLE TIES PART NUMBER			BUNDLE DIAMETER		A	B	C	D	E	F	G	H	I	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	MECHANICAL STRENGTH LBS (n)	MECHANICAL FASTENER SIZE	PLENUM RATING								
			MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .020 (.508mm)														
AP(R, L)-05-30-MH-9			.118 (3.0mm)	1.40 (35.5mm)	6.125 (155.5mm)	.043 (1.09mm)	.14 (3.60mm)	.330 (8.382mm)	.164 (4.165mm)	.155 (3.937mm)	.330 (8.382mm)	.310 (7.874mm)	.039 (.990mm)	40 (180)	V-2	30/133	#8	AH-2								
AP(R, L)-05-30-MH-0			.118 (3.0mm)	1.40 (35.5mm)	6.125 (155.5mm)	.043 (1.09mm)	.14 (3.60mm)	.330 (8.382mm)	.164 (4.165mm)	.155 (3.937mm)	.330 (8.382mm)	.310 (7.874mm)	.039 (.990mm)	40 (180)	V-2	30/133	#8	AH-2								
AP(R, L)-08-50-MH-9			.187 (4.76mm)	1.87 (47.6mm)	8.00 (203.20mm)	.052 (1.320mm)	.177 (4.49mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-08-50-MH-35			.187 (4.76mm)	1.87 (47.6mm)	8.00 (203.20mm)	.052 (1.320mm)	.177 (4.49mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-08-50-MH-0			.187 (4.76mm)	1.87 (47.6mm)	8.00 (203.20mm)	.052 (1.320mm)	.177 (4.49mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-08-50-MH-30			.187 (4.76mm)	1.87 (47.6mm)	8.00 (203.20mm)	.052 (1.320mm)	.177 (4.49mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2	30/135	#10									
AP(R, L)-12-50-MH-9			.187 (4.76mm)	3.06 (77.7mm)	11.50 (292.10mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-12-50-MH-0			.187 (4.76mm)	3.06 (77.7mm)	11.50 (292.10mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-12-50-MH-30			.187 (4.76mm)	3.06 (77.7mm)	11.50 (292.10mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10									
AP(R, L)-15-50-MH-9			.187 (4.76mm)	4.00 (101.6mm)	14.50 (368.30mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-15-50-MH-0			.187 (4.76mm)	4.00 (101.6mm)	14.50 (368.30mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10	AH-2								
AP(R, L)-15-50-MH-30			.187 (4.76mm)	4.00 (101.6mm)	14.50 (368.30mm)	.053 (1.346mm)	.177 (4.49mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2	30/135	#10									
AP(R, L)-15-120-MH-9			.25 (6.35mm)	4.06 (103.1mm)	15.75 (400.05mm)	.075 (1.905mm)	.298 (7.56mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	V-2	60/267	.25"	AH-2								
AP(R, L)-15-120-MH-0			.25 (6.35mm)	4.06 (103.1mm)	15.75 (400.05mm)	.075 (1.905mm)	.298 (7.56mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	V-2	60/267	.25"	AH-2								
AP(R, L)-15-120-MH-30			.25 (6.35mm)	4.06 (103.1mm)	15.75 (400.05mm)	.075 (1.905mm)	.298 (7.56mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	V-2	60/267	.25"									
									ADVANCED CABLE TIES, INC. ADVANCED CABLE TIES – MOUNTING HEAD SERIES CABLE TIES																	
G	7/22/25	DW	JL	JL	UL Specs And Part Number Update																					
F	11/30/23	DW	PR	PR	Addition of 15" 120 lb and 60 lb Mech. Mod.				ADVANCED CABLE TIES – MOUNTING HEAD SERIES CABLE TIES																	
E	10/30/20	DW	RB	RB	14" 120 LB MECHANICAL STRENGTH																					
D	12/19/19	DW	RB	RB	5" MECHANICAL STRENGTH 30 LB			COLOR DESIGNATIONS: 9 = NATURAL & 35 = BURGUNDY 0 = UV BLACK 30 = UV BLACK HEAT STABILIZED					MATERIAL: NYLON 6/6 POLYAMIDE													
C	12/22/17	PB	VA	VA	UPDATED UL SPECS AND ADDED VENDOR SPECS																					
B	5/1/17	JA	KT	KT	NEW LOGO ADDED.			SHEET 1 OF 1		REV.: G		DRAWING NO.: MH-G														
A	12/23/14	JA	KT	KT	INITIAL RELEASE			DRAWN BY		DATE		CHECK		SCALE												
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA		5/1/17		KT		NONE												
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC. THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.																										



ADVANCED CABLE TIES – MOUNTING HEAD SERIES CABLE TIES