


ADVANCED CABLE TIES PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .250 (6.350mm)	B IN (mm) +/- .250 (6.350mm)	C IN (mm) +/- .010 (.254mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .010 (.254mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)							
AP(R,L)-05-50-RL-#	.390 (9.90mm)	1.43 (36.322mm)	5.875 (149.22mm)	5.125 (130.175mm)	.295 (7.493mm)	.308(7.823mm)	.053 (1.346mm)	50 (222)	V-2
AP(R,L)-08-50-RL-#	.390 (9.90mm)	2.19 (55.626mm)	8.031 (203.987mm)	7.187 (182.549mm)	.295 (7.493mm)	.308(7.823mm)	.053 (1.346mm)	50 (222)	V-2
AP(R,L)-12-50-RL-#	.390 (9.90mm)	3.375 (85.725mm)	11.937 (303.199mm)	11.125 (282.575mm)	.295 (7.493mm)	.308(7.823mm)	.053 (1.346mm)	50 (222)	V-2
H	3/10/23	DW	DW	RB	UPDATED TO MANUFACTURED SPECS				
G	7/20/22	DW	DW	RB	REMOVAL OF EXTENDED PAWL PRODUCT LINE				
F	9/7/21	DW	DW	RB	UPDATED B DIMENSIONS				
E	3/7/18	PB	EG	EG	UPDATED UL SPECS AND ADDED VENDOR SPECS				
D	3/6/18	PB	EG	EG	DIMENSION A +/- FROM .125 TO .250, DIMENSION C +/- FROM .005 to .010 AND 14-50-RL DIMENSION A FROM 14.250 TO 14.35				
C	4/29/17	JA	KT	KT	NEW LOGO ADDED				
B	7/26/16	JA	KT	KT	ADDED 7, 11 & 14-50				
A	12/22/14	JA	KT	KT	INITIAL RELEASE				
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	7/26/16	KT	NONE



50 LB. (222n) RELEASABLE CABLE TIES

COLOR DESIGNATIONS: # 0 = UV BLACK 9 = NATURAL **MATERIAL:** **NYLON 6/6 POLYAMIDE**

SHEET 1 OF 1 **REV.: H** DRAWING NO.: RL-H

DRAWN BY DATE CHECK SCALE

JA 7/26/16 KT NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.

THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.59.8