


ADVANCED CABLE TIES PART NUMBER			BUNDLE DIAMETER		A	B	C	D	E	F	G	H	I	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	
			MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .020 (.508mm)			
AL-08-50-MH-IT-30			.187 (4.76mm)	1.750 (44.450mm)	8.000 (203.200mm)	.052 (1.320mm)	.177 (4.495mm)	.364 (9.245mm)	.183 (4.468mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	HB	
AL-15-120-MH-IT-30			.25 (6.35mm)	4.062 (103.174mm)	15.750 (400.050mm)	.075 (1.905mm)	.298 (7.569mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	HB	
								 ADVANCED CABLE TIES, INC.								
								ADVANCED CABLE TIES – HIGH TEMP, UV & IMPACT RESISTANT MOUNTING HEAD SERIES CABLE TIES								
								COLOR DESIGNATIONS:				MATERIAL:				
C	7/23/25	DW	JL	JL				PART NUMBER AND MIN BUNDLE				IT-30 = HIGH TEMP, IMPACT RESISTANT, UV BLACK HEAT STABILIZED				NYLON 6/6 POLYAMIDE
B	4/28/17	JA	KT	KT	NEW LOGO ADDED.			SHEET 1 OF 1		REV.: C		DRAWING NO.: IMPACT-MH-C				
A	4/2/15	JA	KT	KT	INITIAL RELEASE			DRAWN BY		DATE		CHECK		SCALE		
REV	DATE	BY	CHK	APPROVE	DESCRIPTION			JA		4/28/17		KT		NONE		
CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.																
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.																

SPC-4.10.61.2