


ADVANCED CABLE TIES PART NUMBER					A IN (mm) +/- .020 (.520mm)	B IN (mm) +/- .012 (.300mm)	C IN (mm) +/- .012 (.300mm)	D IN (mm) +/- .020 (.520mm)	E IN (mm) +/- .012 (.300mm)	F IN (mm) +/- .012 (.300mm)	ANSI/UL 94 MH FLAMABILITY RATING	
AP(R, L)-AM8-9-C					.748 (18.99mm)	.170 (4.30mm)	.208 (5.28mm)	.375 (9.53mm)	.195 (4.95mm)	.195 (4.96mm)	V-2	
												
						ADVANCED CABLE TIES – ANCHOR MOUNT						
						COLOR DESIGNATIONS: 9 = NATURAL				MATERIAL: NYLON 6/6 POLYAMIDE		
C	12/21/22	DW	RB	RB	MODIFIED DESIGN			SHEET 1 OF 1		REV.: C	DRAWING NO.: AM8-C	
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.			DRAWN BY		DATE	CHECK	SCALE
A	5/13/14	JA	KT	KT	INITIAL RELEASE			JA		4/27/2017	KT	NONE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION							

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.

SPC-4.10.72.2