


ADVANCED CABLE TIES PART NUMBER	A OUTSIDE DIAMETER	B INSIDE DIAMETER	C WALL THICKNESS	D RIGHT HAND PITCH	MAX. OPERATING TEMPERATURE	ABRASION RESISTANCE (TABER) (D1044)	WATER ABSORPTION % (D-570)	DI-ELECTRIC CONSTANT (D-150)	UL COMPLIANCE	REGULATORY COMPLIANCE
AL-CWP-125	.118 +/- .031 (2.997mm +/- .787mm)	.054 +/- .031 (1.372mm +/- .787mm)	.032 +/- .010 (.812mm +/- .254mm)	.187 +/- .062 (4.749mm +/- 1.587mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-187	.166 +/- .031 (4.216mm +/- .787mm)	.106 +/- .031 (2.692mm +/- .787mm)	.030 +/- .010 (.762mm +/- .254mm)	.250 +/- .062 (6.350mm +/- 1.587mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-250	.235 +/- .031 (5.969mm +/- .787mm)	.145 +/- .031 (3.683mm +/- .787mm)	.045 +/- .010 (1.143mm +/- .254mm)	.375 +/- .125 (9.525mm +/- 3.175mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-375	.349 +/- .031 (8.865mm +/- .787mm)	.245 +/- .031 (6.223mm +/- .787mm)	.052 +/- .010 (1.320mm +/- .254mm)	.438 +/- .125 (11.125mm +/- 3.175mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-500	.472 +/- .062 (11.989mm +/- 1.575mm)	.348 +/- .062 (8.839mm +/- 1.575mm)	.062 +/- .010 (1.574mm +/- .254mm)	.563 +/- .125 (14.300 +/- 3.175mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-625	.604 +/- .062 (15.342mm +/- 1.575mm)	.480 +/- .062 (12.192mm +/- 1.575mm)	.062 +/- .010 (1.574mm +/- .254mm)	.625 +/- .250 (15.875mm +/- 6.350mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-750	.713 +/- .062 (18.110mm +/- 1.575mm)	.583 +/- .062 (14.808mm +/- 1.575mm)	.065 +/- .010 (1.651mm +/- .254mm)	.750 +/- .250 (19.050mm +/- 6.350mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
AL-CWP-1000	.964 +/- .093 (24.486mm +/- 2.362mm)	.804 +/- .093 (20.422mm +/- 2.362mm)	.080 +/- .015 (2.032mm +/- .381mm)	1.000 +/- .250 (25.400 +/- 6.350mm)	122°F/50°C	22 mg LOSS PER M CYCLES	.014	2.5	UL RECOGNIZED	RoHS
 ACT ADVANCED CABLE TIES, INC.						ADVANCED CABLE TIES – SPIRAL WRAP				
						COLOR DESIGNATIONS: 0 = UV BLACK 9 = NATURAL		MATERIAL: Low Density Polyethylene		
C	5/5/23	DW	RB	RB	DIMENSIONS & TOLLERANCES					
B	4/27/17	JA	KT	KT	NEW LOGO ADDED.		SHEET 1 OF 1	REV.: C		DRAWING NO.: SPIRAL WRAP-C
A	4/14/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA	4/27/17	KT	NONE

CONFIDENTIAL PROPERTY OF ADVANCED CABLE TIES, INC.
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF ADVANCED CABLE TIES, INC.