



UL Product iQ
 UL'S NEXT GENERATION CERTIFICATIONS SEARCH
 The same trusted data in a modern search engine.

NOW AVAILABLE

▶ LEARN MORE

ZODZ.E168851
Positioning Devices

[Page Bottom](#)

Positioning Devices

[See General Information for Positioning Devices](#)

ACT FASTENING SOLUTIONS A DIV OF ADVANCED CABLE TIES INC

E168851

245 SUFFOLK LN
 GARDNER, MA 01440-1761 USA

Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Mechanical Str., N(lbf)	Operating Temp., °C(°F)		Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
			Min	Max				
AP(R,L)-SM0-(#)	21	222 (50)	-40 (-40)	85 (185)	-	AH-2	V-2	-
AP(R,L)-SM0-0	21	222 (50)	-40 (-40)	85 (185)	Yes	AH-2	V-2	-
AP(R,L)-SM0-30	21	222 (50)	-40 (-40)	125 (257)	-	-	V-2	-
AP(R,L)-SM1-(#)	21	222 (50)	-40 (-40)	85 (185)	-	AH-2	V-2	-
AP(R,L)-SM1-0	21	222 (50)	-40 (-40)	85 (185)	Yes	AH-2	V-2	-
AP(R,L)-SM1-30	21	222 (50)	-40 (-40)	125 (257)	-	-	V-2	-
AP(R,L)-SM2-(#)	21	534 (120)	-40 (-40)	85 (185)	-	AH-2	V-2	-
AP(R,L)-SM2-0	21	534 (120)	-40 (-40)	85 (185)	Yes	AH-2	V-2	-
AP(R,L)-SM2-30	21	534 (120)	-40 (-40)	125 (257)	-	-	V-2	-
AP(R,L)-SM3-(#)	21	534 (120)	-40 (-40)	85 (185)	-	AH-2	V-2	-
AP(R,L)-SM3-0	21	534 (120)	-40 (-40)	85 (185)	Yes	AH-2	V-2	-

AP(R,L)-SM3-30	21	534 (120)	-40 (-40)	125 (257)	-	-	V-2	-
AP(R,L)-SM8-(#)	21	222 (50)	-40 (-40)	85 (185)	-	AH-2	V-2	-
AP(R,L)-SM8-0	21	222 (50)	-40 (-40)	85 (185)	Yes	AH-2	V-2	-
AP(R,L)-SM8-30	21	222 (50)	-40 (-40)	125 (257)	-	-	V-2	-

Integral Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm (in.)		Loop Tensile Str., N (lbf)	Mechanical Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max			Min	Max					
AP(R,L)-07-50-MH-(##)	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50-MH-(#)	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-MH-0	2,21,2S,21S	1.57 (0.06)	47.6 (1.87)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-MH-30	2,21,2S,21S	1.57 (0.06)	47.6 (1.87)	222 (50)	200 (45)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50-MH-(##)	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50-MH-(#)	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-MH-0	2,21,2S,21S	1.57 (0.06)	77.7 (3.06)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-MH-30	2,21,2S,21S	1.57 (0.06)	77.7 (3.06)	222 (50)	200 (45)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50-MH-(##)	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50-MH-(#)	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-MH-0	2,21,2S,21S	1.57 (0.06)	101.6 (4.00)	222 (50)	200 (45)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-MH-30	2,21,2S,21S	1.57 (0.06)	101.6 (4.00)	222 (50)	200 (45)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only

Integral Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm (in.)	Loop Tensile	Mechanical Str., N(lbf)	Operating Temp., °C(°F)	Min. Install.	Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^]
----------	-----------	------------------------	--------------	-------------------------	-------------------------	---------------	-----------------------	---------------	-----------------------	------------------------

				Str., N (lbf)				Temp., °C(°F)				IEC 62275 and EN 62275
		Min	Max			Min	Max					
AP(R,L)-14-120- MH-(#)	2,21	4.74 (0.19)	103.1 (4.06)	534 (120)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Diam., mm(in.)		Loop Tensile Str., N(lbf)	Operating Temp., °C(°F)		Min. Install. Temp., °C(°F)	Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [[^]] IEC 62275 and EN 62275
		Min	Max		Min	Max					
AP(R,L)-04-18- -##	2,21	1.57 (0.06)	22.2 (0.87)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-04-18- -#	2,21	1.57 (0.06)	22.2 (0.87)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-04-18-0	2,21	1.57 (0.06)	22.2 (0.87)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-04-18-30	2,21	1.57 (0.06)	22.2 (0.87)	80 (18)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-04-18-39	2,21	1.57 (0.06)	22.2 (0.87)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-05-40- -##	2,21	1.57 (0.06)	36.5 (1.44)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-05-40- -#	2,21	1.57 (0.06)	36.5 (1.44)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-05-40-0	2,21	1.57 (0.06)	36.5 (1.44)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-05-40-30	2,21	1.57 (0.06)	36.5 (1.44)	178 (40)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-05-40-39	2,21	1.57 (0.06)	36.5 (1.44)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-06-18- -#	2,21	1.57 (0.06)	38.1 (1.50)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-06-18-0	2,21	1.57 (0.06)	38.1 (1.50)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-06-18-30	2,21	1.57 (0.06)	38.1 (1.50)	80 (18)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50- -##	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50-	2,21,2S,21S	1.57	47.6	222 (50)	-40	85	-20 (-4)	-	AH-2	V-2	Type 2 Only

(#)		(0.06)	(1.87)		(-40)	(185)					
AP(R,L)-07-50-0	2,21,2S,21S	1.57 (0.06)	47.6 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-30	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50-32	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50-39	2,21	1.57 (0.06)	47.6 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-07-50-RL- ##	21,21S	1.575 (0.06)	47.625 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	-	V-2	-
AP(R,L)-07-50-RL- #	21,21S	1.575 (0.06)	47.625 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	-
AP(R,L)-07-50-RL- 0	21,21S	1.575 (0.06)	47.625 (1.87)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	-
AP(R,L)-07-50-RL- 30	21,21S	1.575 (0.06)	47.625 (1.87)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-07-50-RL- 32	21,21S	1.575 (0.06)	47.625 (1.87)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-08-120- #	2,21,2S,21S	4.75 (0.19)	52.3 (2.06)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-120-0	2,21,2S,21S	4.75 (0.19)	52.3 (2.06)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-08-120- 30	2,21,2S,21S	4.75 (0.19)	52.3 (2.06)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-08-120- 32	2,21,2S,21S	4.75 (0.19)	52.3 (2.06)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-08-18- #	2,21	1.57 (0.06)	55.5 (2.19)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-18-0	2,21	1.57 (0.06)	55.5 (2.19)	80 (18)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-08-18-30	2,21	1.57 (0.06)	55.5 (2.19)	80 (18)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-08-40- ##	2,21	1.57 (0.06)	60.33 (2.38)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-08-40- #	2,21	1.57 (0.06)	60.33 (2.38)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-40-0	2,21	1.57 (0.06)	60.33 (2.38)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-08-40-30	2,21	1.57 (0.06)	60.33 (2.38)	178 (40)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only

AP(R,L)-08-40-39	2,21	1.57 (0.06)	60.33 (2.38)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-40- (#)	2,21	1.57 (0.06)	85.7 (3.37)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-11-40-0	2,21	1.57 (0.06)	85.7 (3.37)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-11-40-30	2,21	1.57 (0.06)	85.7 (3.37)	178 (40)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50- (##)	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50- (#)	2,21,2S,21S	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-0	2,21,2S,21S	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-30	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50-32	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50-39	2,21	1.57 (0.06)	77.7 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-11-50-RL- (##)	21,21S	1.575 (0.06)	77.775 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	-	V-2	-
AP(R,L)-11-50-RL- (#)	21,21S	1.575 (0.06)	77.775 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	-
AP(R,L)-11-50-RL- 0	21,21S	1.575 (0.06)	77.775 (3.06)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	-
AP(R,L)-11-50-RL- 30	21,21S	1.575 (0.06)	77.775 (3.06)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-11-50-RL- 32	21,21S	1.575 (0.06)	77.775 (3.06)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-14-120- (##)	2,21	4.75 (0.19)	103.1 (4.06)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-120- (#)	2,21,2S,21S	4.75 (0.19)	103.1 (4.06)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-120-0	2,21,2S,21S	4.75 (0.19)	103.1 (4.06)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-14-120- 30	2,21,2S,21S	4.75 (0.19)	103.1 (4.06)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-120- 32	2,21,2S,21S	4.75 (0.19)	103.1 (4.06)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-120-	2,21	4.75	103.1	534 (120)	-40	85	-20 (-4)	Yes	-	V-2	Type 2 Only

39		(0.19)	(4.06)		(-40)	(185)					
AP(R,L)-14-40- (#)	2,21	1.57 (0.06)	101.6 (4.00)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-40-0	2,21	1.57 (0.06)	101.6 (4.00)	178 (40)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-14-40-30	2,21	1.57 (0.06)	101.6 (4.00)	178 (40)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50- (#)	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50- (#)	2,21,2S,21S	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-0	2,21,2S,21S	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-30	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50-32	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50-39	2,21	1.57 (0.06)	101.6 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-14-50-RL- (#)	21,21S	1.575 (0.06)	101.60 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	-	V-2	-
AP(R,L)-14-50-RL- (#)	21,21S	1.575 (0.06)	101.60 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	-
AP(R,L)-14-50-RL- 0	21,21S	1.575 (0.06)	101.60 (4.00)	222 (50)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	-
AP(R,L)-14-50-RL- 30	21,21S	1.575 (0.06)	101.60 (4.00)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-14-50-RL- 32	21,21S	1.575 (0.06)	101.60 (4.00)	222 (50)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	-
AP(R,L)-18-120- (#)	2,21,2S,21S	4.75 (0.19)	127 (5.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-18-120-0	2,21,2S,21S	4.75 (0.19)	127 (5.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-18-120- 30	2,21,2S,21S	4.75 (0.19)	127 (5.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-18-120- 32	2,21,2S,21S	4.75 (0.19)	127 (5.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-24-120- (#)	2,21,2S,21S	4.75 (0.19)	177.8 (7.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-24-120-0	2,21,2S,21S	4.75 (0.19)	177.8 (7.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only

AP(R,L)-24-120-30	2,21,2S,21S	4.75 (0.19)	177.8 (7.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-24-120-32	2,21,2S,21S	4.75 (0.19)	177.8 (7.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-24-175- (#)	2,21	38.1 (1.50)	182.3 (7.18)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-24-175-0	2,21	38.1 (1.50)	182.3 (7.18)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-30-120- (#)	2,21,2S,21S	4.75 (0.19)	228.6 (9.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-30-120-0	2,21,2S,21S	4.75 (0.19)	228.6 (9.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-30-120-30	2,21,2S,21S	4.75 (0.19)	228.6 (9.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-30-120-32	2,21,2S,21S	4.75 (0.19)	228.6 (9.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-33-175- (#)	2,21	38.1 (1.50)	247.6 (9.75)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-33-175-0	2,21	38.1 (1.50)	247.6 (9.75)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-36-120- (#)	2,21,2S,21S	4.75 (0.19)	279.4 (11.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-36-120-0	2,21,2S,21S	4.75 (0.19)	279.4 (11.00)	534 (120)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-36-120-30	2,21,2S,21S	4.75 (0.19)	279.4 (11.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-36-120-32	2,21,2S,21S	4.75 (0.19)	279.4 (11.00)	534 (120)	-40 (-40)	125 (257)	-20 (-4)	Yes	-	V-2	Type 2 Only
AP(R,L)-36-175- (#)	2,21	38.1 (1.50)	279.4 (11.00)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-36-175-0	2,21	38.1 (1.50)	279.4 (11.00)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only
AP(R,L)-48-175- (#)	2,21	38.1 (1.50)	368.3 (14.50)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	-	AH-2	V-2	Type 2 Only
AP(R,L)-48-175-0	2,21	38.1 (1.50)	368.3 (14.50)	778 (175)	-40 (-40)	85 (185)	-20 (-4)	Yes	AH-2	V-2	Type 2 Only

[^] - Eligible to be marked "IEC 62275" and "EN 62275" on Type 2 products only.

(##) - Where ## may be replace with 1-29, 33-38, 42-48, 71-78 denoting UV color.

(#) - Where # may be replaced with 1-29, 33-38, 42-48, 71-78 denoting color.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".