

ZODZ.E168851 - Positioning Devices

Positioning Devices

ACT FASTENING SOLUTIONS A DIV OF ADVANCED CABLE TIES INC
 245 SUFFOLK LN
 GARDNER, MA 01440-1761 United States

E168851

Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Mechanical Str., N(lbf)	Operating Temp., °C		Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
			Min	Max				
AP(R,L)-SM0- (#)	21	222	-40	85	-	AH-2	V-2	-
AP(R,L)-SM0-0	21	222	-40	85	Y	AH-2	V-2	-
AP(R,L)-SM0-30	21	222	-40	125	-	-	V-2	-
AP(R,L)-SM1- (#)	21	222	-40	85	-	AH-2	V-2	-
AP(R,L)-SM1-0	21	222	-40	85	Y	AH-2	V-2	-
AP(R,L)-SM1-30	21	222	-40	125	-	-	V-2	-
AP(R,L)-SM2- (#)	21	534	-40	85	-	AH-2	V-2	-
AP(R,L)-SM2-0	21	534	-40	85	Y	AH-2	V-2	-
AP(R,L)-SM2-30	21	534	-40	125	-	-	V-2	-
AP(R,L)-SM3- (#)	21	534	-40	85	-	AH-2	V-2	-
AP(R,L)-SM3-0	21	534	-40	85	Y	AH-2	V-2	-
AP(R,L)-SM3-30	21	534	-40	125	-	-	V-2	-
AP(R,L)-SM8- (#)	21	222	-40	85	-	AH-2	V-2	-
AP(R,L)-SM8-0	21	222	-40	85	Y	AH-2	V-2	-

AP(R,L)-SM8-30	21	222	-40	125	-	-	V-2	-
----------------	----	-----	-----	-----	---	---	-----	---

Integral Fixing Devices Investigated to ANSI/UL 62275

Cat. No.	Type Dsg.	Bundle Dia., mm		Loop Tensile Str., N	Mechanical Str., N(lbf)	Operating Temp., °C		Min. Install. Temp., °C	Resistant to UV Light	Plenum Rating	Material Flame Rating	Also Classified to [^] IEC 62275 and EN 62275
		Min	Max			Min	Max					
		AP(R,L)-07-50-MH-##	2,21			1.57	47.6					
AP(R,L)-07-50-MH-#	2,21	1.57	47.6	222	200	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-MH-0	2,21,2S,21S	1.57	47.6	222	200	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-MH-30	2,21,2S,21S	1.57	47.6	222	200	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-MH-##	2,21	1.57	77.7	222	200	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-MH-#	2,21	1.57	77.7	222	200	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-MH-0	2,21,2S,21S	1.57	77.7	222	200	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-MH-30	2,21,2S,21S	1.57	77.7	222	200	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-MH-##	2,21	1.57	101.6	222	200	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-MH-#	2,21	1.57	101.6	222	200	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-MH-0	2,21,2S,21S	1.57	101.6	222	200	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-MH-30	2,21,2S,21S	1.57	101.6	222	200	-40	125	-20	Y	-	V-2	Type 2 Only

Nonmetallic Cable Ties Investigated to ANSI/UL 62275

**Also
Classified
to [^]
IEC
62275
and EN
62275**

Cat. No.	Type Dsg.	Bundle Dia., mm		Loop Tensile Str., N	Operating Temp., °C		Min. Install. Temp., °C	Resistant to UV Light	Plenum Rating	Material Flame Rating	
		Min	Max		Min	Max					
AP(R,L)-04-18-##	2,21	1.57	22.2	80	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-04-18-#	2,21	1.57	22.2	80	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-04-18-0	2,21	1.57	22.2	80	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-04-18-30	2,21	1.57	22.2	80	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-04-18-39	2,21	1.57	22.2	80	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-05-40-##	2,21	1.57	36.5	178	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-05-40-#	2,21	1.57	36.5	178	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-05-40-0	2,21	1.57	36.5	178	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-05-40-30	2,21	1.57	36.5	178	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-05-40-39	2,21	1.57	36.5	178	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-06-18-#	2,21	1.57	38.1	80	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-06-18-0	2,21	1.57	38.1	80	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-06-18-30	2,21	1.57	38.1	80	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-07-50-##	2,21	1.57	47.6	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-07-50-#	2,21,2S,21S	1.57	47.6	222	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-0	2,21,2S,21S	1.57	47.6	222	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-07-50-30	2,21	1.57	47.6	222	-40	125	-20	Y	-	V-2	Type 2 Only

AP(R,L)-07-50-32	2,21	1.57	47.6	222	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-07-50-39	2,21	1.57	47.6	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-07-50-RL-(##)	21,21S	1.575	47.625	222	-40	85	-20	-	-	V-2	-
AP(R,L)-07-50-RL-(#)	21,21S	1.575	47.625	222	-40	85	-20	-	AH-2	V-2	-
AP(R,L)-07-50-RL-0	21,21S	1.575	47.625	222	-40	85	-20	Y	AH-2	V-2	-
AP(R,L)-07-50-RL-30	21,21S	1.575	47.625	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-07-50-RL-32	21,21S	1.575	47.625	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-08-120-(#)	2,21,2S,21S	4.75	52.3	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-120-0	2,21,2S,21S	4.75	52.3	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-08-120-30	2,21,2S,21S	4.75	52.3	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-08-120-32	2,21,2S,21S	4.75	52.3	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-08-18-(#)	2,21	1.57	55.5	80	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-18-0	2,21	1.57	55.5	80	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-08-18-30	2,21	1.57	55.5	80	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-08-40-(##)	2,21	1.57	60.33	178	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-08-40-(#)	2,21	1.57	60.33	178	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-08-40-0	2,21	1.57	60.33	178	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-08-40-30	2,21	1.57	60.33	178	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-08-40-39	2,21	1.57	60.33	178	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-40-(#)	2,21	1.57	85.7	178	-40	85	-20	-	AH-2	V-2	Type 2 Only

AP(R,L)-11-40-0	2,21	1.57	85.7	178	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-11-40-30	2,21	1.57	85.7	178	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-(##)	2,21	1.57	77.7	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-(#)	2,21,2S,21S	1.57	77.7	222	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-0	2,21,2S,21S	1.57	77.7	222	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-11-50-30	2,21	1.57	77.7	222	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-32	2,21	1.57	77.7	222	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-39	2,21	1.57	77.7	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-11-50-RL-(##)	21,21S	1.575	77.775	222	-40	85	-20	-	-	V-2	-
AP(R,L)-11-50-RL-(#)	21,21S	1.575	77.775	222	-40	85	-20	-	AH-2	V-2	-
AP(R,L)-11-50-RL-0	21,21S	1.575	77.775	222	-40	85	-20	Y	AH-2	V-2	-
AP(R,L)-11-50-RL-30	21,21S	1.575	77.775	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-11-50-RL-32	21,21S	1.575	77.775	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-14-120-(##)	2,21	4.75	103.1	534	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-120-(#)	2,21,2S,21S	4.75	103.1	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-120-0	2,21,2S,21S	4.75	103.1	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-14-120-30	2,21,2S,21S	4.75	103.1	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-120-32	2,21,2S,21S	4.75	103.1	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-120-39	2,21	4.75	103.1	534	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-40-(#)	2,21	1.57	101.6	178	-40	85	-20	-	AH-2	V-2	Type 2 Only

AP(R,L)-14-40-0	2,21	1.57	101.6	178	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-14-40-30	2,21	1.57	101.6	178	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-(##)	2,21	1.57	101.6	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-(#)	2,21,2S,21S	1.57	101.6	222	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-0	2,21,2S,21S	1.57	101.6	222	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-14-50-30	2,21	1.57	101.6	222	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-32	2,21	1.57	101.6	222	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-39	2,21	1.57	101.6	222	-40	85	-20	Y	-	V-2	Type 2 Only
AP(R,L)-14-50-RL-(##)	21,21S	1.575	101.60	222	-40	85	-20	-	-	V-2	-
AP(R,L)-14-50-RL-(#)	21,21S	1.575	101.60	222	-40	85	-20	-	AH-2	V-2	-
AP(R,L)-14-50-RL-0	21,21S	1.575	101.60	222	-40	85	-20	Y	AH-2	V-2	-
AP(R,L)-14-50-RL-30	21,21S	1.575	101.60	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-14-50-RL-32	21,21S	1.575	101.60	222	-40	125	-20	Y	-	V-2	-
AP(R,L)-18-120-(#)	2,21,2S,21S	4.75	127	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-18-120-0	2,21,2S,21S	4.75	127	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-18-120-30	2,21,2S,21S	4.75	127	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-18-120-32	2,21,2S,21S	4.75	127	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-24-120-(#)	2,21,2S,21S	4.75	177.8	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-24-120-0	2,21,2S,21S	4.75	177.8	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-24-120-30	2,21,2S,21S	4.75	177.8	534	-40	125	-20	Y	-	V-2	Type 2 Only

AP(R,L)-24-120-32	2,21,2S,21S	4.75	177.8	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-24-175-(#)	2,21	38.1	182.3	778	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-24-175-0	2,21	38.1	182.3	778	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-30-120-(#)	2,21,2S,21S	4.75	228.6	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-30-120-0	2,21,2S,21S	4.75	228.6	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-30-120-30	2,21,2S,21S	4.75	228.6	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-30-120-32	2,21,2S,21S	4.75	228.6	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-33-175-(#)	2,21	38.1	247.6	778	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-33-175-0	2,21	38.1	247.6	778	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-36-120-(#)	2,21,2S,21S	4.75	279.4	534	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-36-120-0	2,21,2S,21S	4.75	279.4	534	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-36-120-30	2,21,2S,21S	4.75	279.4	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-36-120-32	2,21,2S,21S	4.75	279.4	534	-40	125	-20	Y	-	V-2	Type 2 Only
AP(R,L)-36-175-(#)	2,21	38.1	279.4	778	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-36-175-0	2,21	38.1	279.4	778	-40	85	-20	Y	AH-2	V-2	Type 2 Only
AP(R,L)-48-175-(#)	2,21	38.1	368.3	778	-40	85	-20	-	AH-2	V-2	Type 2 Only
AP(R,L)-48-175-0	2,21	38.1	368.3	778	-40	85	-20	Y	AH-2	V-2	Type 2 Only

(##) - Where ## may be replace with 1-29, 33-38, 42-48, 71-78 denoting UV color.

(#) - Where # may be replaced with 1-29, 33-38, 42-48, 71-78 denoting color.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"